

## ALUTRUSS BILOCK E-GL22 3000 Traversa a 2 punti

Sistema di traverse a 2 punti

Art.n.: 60302095

GTIN: 4026397572681



### Descrizione :

BILOCK E-GL22 2-point truss system

BILOCK E-GL22 is a 2-point truss system made of aluminum. The individual elements are connected via two cones, pivots and pins.

The advantage of the conical connection system is that the cones completely fit into the main chords so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The two main chords are made of 50 mm aluminum tube with 2 mm wall thickness and offer a good relation between strength and weight. The braces have a diameter of 20 mm with 2 mm wall thickness and leave enough space for installing couplers, hooks and clamps.

With 290 mm outer dimensions, BILOCK E-GL22 is a stable truss system for higher loads and extended durability. This system is mainly designed for intense use in stage installations, fair installations, event installations but also for permanent installations in discotheques and theatres.

Its polished surface makes this universal system a real eyecatcher. Due to its wide range of standard system lengths, corners, circles and accessory, this system is highly versatile and offers unlimited design possibilities.

The documentation of this truss system is closely related to the Codes of Practice SQ P1 - Truss Systems published by the VPLT/PLASA. The load table as calculation base can be downloaded from the Internet before buying the product!

### Logistica

EAN / GTIN: 4026397572681

Peso : 7,70 kg

Lunghezza : 3.00 m

Larghezza : 0.30 m

Altezza : 0.05 m

Merci voluminose

**Features :**

---

- Peso leggero
- Montaggio facile
- Tubo della cinghia: 50 mm
- Made in Europe
- Per campi di applicazione come, ad esempio,: Teatro; Allestimenti per fiere e negozi; club/scuole di danza
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

**Dati tecnici :**

---

|                                  |                                                           |
|----------------------------------|-----------------------------------------------------------|
| Struttura:                       | Montaggio facile                                          |
| Tubo della cinghia:              | 50 mm x 2 mm                                              |
| Processo di saldatura:           | Impulso TIG                                               |
| Materiale di saldatura:          | AlMg 5                                                    |
| Materiale del tubo:              | AlSi1MgMn                                                 |
| Colore:                          | Color alluminio                                           |
| Spessore x diametro del puntone: | 20 x 2mm                                                  |
| Misure:                          | Lunghezza: 300 cm<br>Larghezza: 29 cm<br>Profondità: 5 cm |
| Peso:                            | 6,70 kg                                                   |

**Contenuto della confezione:**

---

1 x set di connettori