

EUROLITE LSD-18.25 IP44 (H)1,17m (W)1,17m

LED soft displays

Art.n.: 80503222

GTIN: 4026397453218



L'articolo non è più disponibile.

Features :

- Flexible displays with tri-color RGB LEDs (type SMD 5050) for bright and colorful projection of videos and graphics
- Modular display concept allows the build-up of large areas, ideal for outdoor use with large viewing distances
- Bendable and foldable PVC material suitable for various shapes, e.g. columns, circles, angles
- Fast and uncomplicated installation, indoor and outdoor (IP44)
- Truss suspension via built-in belts
- Water-repellent and flame-resistant
- Low weight and small volume for convenient transport
- Easy maintenance - LEDs can be replaced without difficulty
- Controllable via optional network components and PC software
- All-in-one control system T9 (80503301): network interface and software LED Show T9 - ideal system for mobile use with notebooks with 1-gigabit NIC
- Control system LED studio: receiver interface (80503311), PCI sending card and software LED Studio (80503130)
- Recommended media software: MADRIX
- Switch-mode power supply for operation between 100 and 240 Volts
- Power output for passing on the power supply
- Available in different sizes and pixel pitches
- Custom sizes available upon request
- 4096 LED SMD 5050 3in1 RGB (miscela di colori omogenea)

Logistica

EAN / GTIN: 4026397453218

Peso : 18,40 kg

Lunghezza : 1.23 m

Larghezza : 0.62 m

Altezza : 0.14 m

Merci voluminose

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	100,00 W
Grado di protezione:	IP44
Tipo di LED:	4096 x SMD 5050 3in1 RGB (miscela di colori omogenea)
Durata utile:	100000 h
Misure:	Larghezza: 117 cm Altezza: 117 cm
Peso:	16,15 kg
Resolution (W x H):	64 x 64 pixels
Pixel pitch:	18.25 mm
Pixel density:	3002/m²
Pixel configuration:	tri-color RGB LEDs, type SMD 5050
Display port:	DVI/RJ45
Display mode:	synchronous to video source
Drive mode:	1/8 scan
Screen resolution:	max. 1280 x 1024 (LED Studio) max. 1024 x 896 (LED Show T9)
Brightness:	3680 cd/m² (nits)
Viewing angle:	120°
Frame rate:	60 Hz
Data refresh rate:	600 Hz
Colors:	16.7 million (R 256, G 256, B 256)
Operating temperature:	-10 to 45 °C
Humidity:	10 to 90 %

Contenuto della confezione: