



Prezzo di listino: 62.48 €
incl. 19% IVA

Features :

- For switching four AV sources (audio, composite video and s-video television signals) up to two television monitors
- 4 inputs (RCA), manually or automatically switchable
- Automatic switching time adjustable from 1 to 25 seconds
- Simultaneous recording to one or two video or DVD recorders
- A HiFi stereo system can be connected via the second output
- Per campi di applicazione come, ad esempio,: Allestimenti per fiere e negozi; club/scuole di danza; Ristoranti, bar e hotel

Logistica

EAN / GTIN: 4026397306613
Peso : 0,90 kg
Lunghezza : 0.31 m
Larghezza : 0.13 m
Altezza : 0.06 m

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	6,00 W
Intervallo di frequenza:	20 - 100 Hz
Rapporto segnale-rumore:	>100 dB
Distorzione armonica totale:	<0,05 % a 1 kHz
Misure:	Larghezza: 24,2 cm Profondità: 12,8 cm Altezza: 5 cm
Peso:	0,75 kg
Video:	

4 x inputs:	1 Vpp/ 75 ohms, composite RCA
2 x outputs:	1 Vpp/ 75 ohms, composite RCA
Gain:	2 V, 1 V (terminated)/ 75 ohms
Return loss:	>18 dB
Video bandwidth:	>100 MHz
Audio:	
4 x inputs:	22 kohms, stereo RCA
2 x output:	1 kohms, stereo RCA
Gain:	nominal 0 dB
Channel separation:	>75 dB

Contenuto della confezione: