



### Features:

#### ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### ALUTRUSS Truss Transport Board Combo incl. 3 Wheels

Transport cart with castors for QUADLOCK and TRILOCK truss elements

- The article is delivered dismantled

#### ALUTRUSS Truss Transport Ridge Combo

Stacking rail for QUADLOCK and TRILOCK truss elements

- Stacking ridge for quick and secure stacking of truss elements on matching transport carts
- Suitable for QUADLOCK and TRILOCK truss elements with 290 mm
- Made in Germany

### Logistic

### SHZ Clamping Belt S400 Ratchet 5m/25mm black

Clamping belt

- LC400/800daN surroundings
- Complies with EN 12195-2
- Ratchet lock

### Technical specifications:

---

Weight: 100.38 kg

---

### ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

Setup: Easy installation

---

Trusspipe: 50 mm x 2 mm

---

Welding technique: TIG-welding

---

Welding material: AlMg 5

---

Alloy: AlMgSi1 T6

---

Color: Alu colored

---

Strut diameter x thickness: 16 x 2mm

---

Dimensions: Length: 200 cm  
Width: 29 cm  
Height: 29 cm

---

Weight: 10.80 kg

---

### ALUTRUSS Truss Transport Board Combo incl. 3 Wheels

Weight: 3.60 kg

---

### ALUTRUSS Truss Transport Ridge Combo

Material: Birch multiplex, 30 mm

---

Dimensions: Length: 60 cm  
Width: 3 cm  
Depth: 5 cm

---

Weight: 0.50 kg

---

### SHZ Clamping Belt S400 Ratchet 5m/25mm black

Standard: EN 12195-2,

---

Lock: Ratchet lock

---

Color: Black

---

Dimensions: Length: 500 cm  
Width: 2.50 cm

---

Weight: 0.30 kg

---

**Scope of delivery:**

---

1 x connection set