



---

**Features:**

---

**Logistic****OMNITRONIC RS-602 Recording Mixer**

Compact 6-channel studio and live mixer

- Low-noise 6-channel mic/line mixer
- 2 mono inputs with XLR sockets, +48V phantom power and balanced line inputs
- 2 stereo inputs with balanced 6.3 mm jack sockets
- Stereo inputs can also be operated mono
- 3-band EQ for all inputs
- Peak LED per mono input
- Aux send per channel for controlling external effectors
- Stereo aux return with balanced 6.3 mm jack sockets
- Separate main mix, booth and headphones outputs
- Tape inputs assignable to master, booth/headphones
- Precise 10-fold stereo LED meter

**OMNITRONIC M-22 Dynamic Microphone**

Unidirectional microphone with 3 m jack cable

- Dynamic handheld microphone for studio and stage use
- On/off switch
- Excellent quality at a low price
- 3 m jack cable attached to microphone
- Polar pattern: Cardioid

**OMNITRONIC SHP-2000 MK2 DJ Headphones**

Convenient DJ stereo headphones

- Closed dynamic stereo headphones for DJs
- 50 mm driver
- Distortion-free playback also at a high volume
- Optimal wearer-comfort due to single cable (L)
- Well-padded, adjustable headband
- Oversized earpieces for screening undesired noise
- Space-saving design with collapsible, rotating (180°) earcups
- Detachable connection cable with gold-plated 3.5 mm stereo jack
- Rugged workmanship for discotheque and stage use
- Incl. 6.3 mm jack adapter and bag

## Technical specifications:

---

Weight: 3.07 kg

---

### OMNITRONIC RS-602 Recording Mixer

Power consumption: 15.00 W

---

Dimensions: Width: 22 cm  
Depth: 25 cm  
Height: 5.5 cm

---

Weight: 2.40 kg

---

Power supply: 2 x 20 V AC, 50/60 Hz  
via included power unit

---

#### Inputs:

2 x mono XLR or balanced 6.3 mm jack

---

2 x stereo balanced 6.3 mm jacks

---

1 x Aux Return: balanced 6.3 mm jacks

---

1 x Tape In stereo RCA

---

#### Outputs:

1 x Master Out balanced 6.3 mm jacks

---

1 x Control Room balanced 6.3 mm jacks

---

1 x Aux Send: balanced 6.3 mm jacks

---

1 x Tape Out stereo RCA

---

#### Frequency range:

Microphone: 10-60000 Hz,  $\pm 3$  dB

---

Mono: 10-60000 Hz,  $\pm 3$  dB

---

Stereo: 10-55000 Hz,  $\pm 3$  dB

---

Distortion: 0.01 %

---

S/N ratio: 112 dB

---

#### Tone control/channel:

Treble:  $\pm 15$  dB at 12 kHz

---

Middle:  $\pm 15$  dB at 2.5 kHz

---

Bass:  $\pm 15$  dB at 80 Hz

---

Dimensions (W x D x H): 220 x 250 x 55 mm

---

### OMNITRONIC M-22 Dynamic Microphone

Type:	Vocal microphone
Capsule type:	Dynamic
Polar pattern:	Cardioid
Frequency range:	50 - 13000 Hz
Sensitivity:	-53 dB
Impedance:	500 Ohm
Connections:	Microphone via 6.3 mm plug (unbal.)
Switch:	On/off switch
Dimensions:	Length: 22 cm Diameter: Ø 5.5 cm
Weight:	0.23 kg
Dimensions:	Length: 300 cm

### OMNITRONIC SHP-2000 MK2 DJ Headphones

Cable length:	1.2 m
Frequency range:	20 - 20000 Hz
Sensitivity:	95 dB
Max. SPL:	95 dB
Rated power:	200 mW
Connector type:	3.5 mm jack (stereo); 6.3 mm jack (stereo)
Connections:	Headphones via 6.3 mm jack (stereo) Headphones via 3.5 mm jack (stereo)
Transducer type:	Dynamic
Type (headphones):	Closed
Weight:	0.44 kg

### Scope of delivery:

- 1 x adapter cable
- 1 x microphone