



Features:

EUROLITE LED PAR-56 COB RGB 100W bk

PAR spot with 100 W COB LED and RGB color mixing

- Stepless color blend, color change, dimmer and strobe effect
- Dimmer speed (step response) adjustable
- Stand-alone or DMX mode
- Locking possibility at the mounting bracket
- With color filter frame
- Various versions available
- 1 LED 100 W COB (chip-on-board) 3in1 R/G/B (homogenous color mix)
- Strobe effect
- Control via DMX; sound to light via microphone
- Fixtures available for Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- With a beam angle of 40°
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EUROLITE TB-4X T-Bar

For problem-free installations

- Makes the installation of your lighting system really easy
- Fully wired with DMX-splitter
- 1.50 meters
- With 4 spot connections
- With 4 flap safety-plugs
- With 4 DMX connectors

- Connection via Powercon In/Out-socket

Technical specifications:

Weight:	16.30 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED PAR-56 COB RGB 100W bk

Power supply:	230 V AC, 50 Hz
Power consumption:	130 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 1 m
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) 3in1 R/G/B (homogenous color mix)
DMX channels:	3; 5
Control:	DMX; sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Beam angle (1/2 peak):	40°
Housing color:	Black
Dimensions:	Width: 24 cm Depth: 36.5 cm Height: 31.5 cm
Weight:	2.90 kg
Noise classification:	Class 2 (slight noise)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE TB-4X T-Bar

Power supply:	230 V AC, 50 Hz
Output current:	Max. 10 A per channel
Dimensions:	Length: 150 cm Width: 7.5 cm Height: 16.5 cm
Weight:	4.70 kg
Max. power output:	2300 W
Max. total current:	10 A
Max. output/channel:	2300 W

Max. current/channel:	10 A
Maximum load per fixation point:	7.5 kg
Max. spaced braced load:	30 kg
Dimensions (L x W x H):	1500 x 75 x 165 mm

Scope of delivery:
