

### Features:

---

#### EUROLITE LED SLS-3 HCL 3x10W Floor

Slimline LED spot with 3 x 10 W 5in1 LED

- Operable in stand-alone mode or via DMX interface
- DMX512 control possible via any commercial DMX controller (occupies max. 9 channels)
- Master/Slave for parallel operation of several devices
- 6, 7, 8 or 9 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Equipped with 6in1 hexacolor LEDs for homogeneous light output in the colors red, green, blue, amber, white and UV
- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Functions: Static colors, RGBAW+UV color blend, internal programs, dimmer, strobe, sound-control, microphone sensitivity, color macros
- Further display settings: display on or off, display inverted, default settings
- Comfortable addressing and setting via control panel with 4-digit LED screen and four operating buttons
- Ready for connection via IEC power cord with safety-plug
- Feed-through output allows to power up to 8 devices
- Switch-mode power supply for operation between 100 and 240 volts
- Fixtures available for Light'J; Light Captain

#### EUROLITE DMX LED Operator 6 Controller

Simple controller for 6 RGBWA+UV LED spots

- DMX controller for easy operation of standard 6-channel LED spots

### Logistic

---

- 6 spots or light effect units with RGBWA+UV LEDs can be controlled
- 6 DMX channels (red/green/blue/white/amber/UV) can be controlled per unit
- Sequence of white and amber function freely selectable
- 6 trigger buttons for direct color selection and preset chases
- 18 trigger buttons for color presets
- Internal memory for 1 scene
- Auto, fade and macro mode
- Fade and speed time can be adjusted separately
- Master fader
- Strobe function with adjustable speed
- Blackout function
- Desktop console
- Can transmit up to 36 DMX channels
- Control via DMX; sound to light via microphone
- Desktop console housing

### ROADINGER Flightcase 4x SLS Size M

Trunk case, PRO version

- Individually adjustable and removable dividers for universal use
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

---

#### EUROLITE LED SLS-3 HCL 3x10W Floor

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	24.00 W
Fixtures available for:	Light J; Light Captain
Dimensions:	Width: 11.5 cm Depth: 21 cm Height: 22.5 cm
DMX channels:	6/7/8/9
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	10 W HCL
LED number:	3
Beam angle:	40°
Dimensions (W x D x H):	115 x 210 x 225 mm
Weight:	2 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### EUROLITE DMX LED Operator 6 Controller

Power supply:	100-240 V AC, 50/60 Hz
Pin configuration:	Inside + / outside -
Power consumption:	4 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
DMX channels:	Output 36
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via microphone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 40 cm Depth: 15 cm Height: 7 cm
Weight:	1.60 kg

#### **ROADINGER Flightcase 4x SLS Size M**

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	12 cm x 25 cm x 35.5 cm
Inside dimensions:	49.5 cm x 25 cm x 35.5 cm
Dimensions:	Width: 52.5 cm Depth: 28.5 cm Height: 44.5 cm
Weight:	7.65 kg

#### **OMNITRONIC XLR Cable 3-pin 5m bk**

Cable construction:	2 x 0.22 mm <sup>2</sup> microphone cable
Cable length:	5 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Dimensions:	Diameter: Ø 0.60 cm
Weight:	0.24 kg
Material:	Metal

**OMNITRONIC XLR Cable 3-pin 10m bk**

Cable construction:	Audio cable
Cable length:	10 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	0.46 kg

**Scope of delivery:****3 x OMNITRONIC XLR Cable 3-pin 5m bk**

1 x XLR cable

**1 x OMNITRONIC XLR Cable 3-pin 10m bk**

1 x XLR cable