



The article is no longer in our assortment.

Features:

EUROLITE LED PIX-8 QCL Bar

Compact LED color changing bar with 8 x 8 W 4in1 LED

- Equipped with eight QCL LEDs in the colors red, green, blue and white
- Particularly bright illuminating power of the LEDs
- 4, 6, 7, 11, 19, 32, 35 DMX channels selectable for various applications
- Each LED can be controlled individually
- Programmable color change speed, strobe effect and dimmer
- Strobe effect with 1-18 flashes per second
- RGBW color mixing
- Static colors
- Internal programs
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Manual, sound or DMX-controlled operation
- For large stage backgrounds in public places, main halls and lounges
- Hanging as well as standing installation possible
- Locking possibility at the mounting bracket
- Sound-controlled via built-in microphone
- Addressing via control panel with LCD screen
- Ready for connection with power-cable and plug
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- DMX512 control possible via any commercial DMX controller
- Control via DMX
- Preprogrammed in Light´J; LED PC-Control 512

Logistic

MADRIX NEO - USB DMX512 interface

MADRIX USB/DMX interface to issue a DMX universe over XLR

- MADRIX NEO is a reliable, easy-to-use, and high-quality DMX512 USB hardware interface including MADRIX software for LED control and MADRIX 3 software license
 - The interface can be used for DMX input or DMX output to connect DMX512 devices to your computer
 - The MADRIX software license for 512 DMX channels per device is already included and automatically activated when connected to MADRIX
 - If you want to use DMX-IN, please use a 5-pin XLR male to 5-pin XLR male gender changer
 - The MADRIX 3 Software license for 512 DMX channels per device is already included and automatically activated when connected to MADRIX
 - Full USB 2.0 support, Power over USB, Hot Swapping, and Plug & Play
 - Multiple devices can be used together without problems for larger projects
 - Rugged metal housing with eye-catching design
 - MADRIX is a powerful, easy-to-use, and award-winning LED lighting control software
 - Allows you to realize all kinds of different LED projects and lighting designs
 - A normal PC/laptop can be used for professional LED control
 - Allows mapping in 2D (pixel mapping) as well as real, spatial 3D (voxel mapping)
 - The software generates unique effects, visuals, and animations live and in real time
 - No additional content is required
 - Already includes a multitude of stock effects that are fully customizable (in speed, color, shape, direction, size, movement, position, brightness etc.)
 - Analyzes incoming audio signals Sound2Light and Music2Light in real time
 - New lighting scenes can easily be created in seconds
 - Variety of options to combine visuals and graphical elements (layers, mix modes, filters, etc.)
 - 256 x 256 Storage Places to organize and store effects
 - DJ-like operation with 2 decks (Left/Right) and a crossfader
 - 3 real-time previews to show your visual effects in advance (incl. 2D/3D, zoom, rotation)
 - Controls up to 4 color channels per pixel/voxel (e.g. 1-channel, 2-channel, RGB, RGBW fixtures)
 - Freely configurable Cue List for automated playback of a show (incl. time, date, duration, etc.)
 - Supports Time Code from Art-Net, MIDI, SMPTE, and system time
 - Remote control available via DMX-IN, Art-Net Remote, MIDI-IN, HTTP (internet browser), CIP
 - Incl. Fixture Editor with large fixture library
 - Includes various other tools and features (DMX Fader Tool, DMX Watcher, Matrix Generator, Patch Editor, Touch Screen window, backup system, scripting, mapping, scaling, etc.)
 - MADRIX minimum system requirements: 2.0 GHz dual-core CPU, OpenGL 2.0 graphics card (NVIDIA recommended), 2 GB RAM, 1 GB free harddisk space, 1280 x 768 screen resolution, network card, sound card, USB 2.0
 - Installation instructions and software available in English, Spanish, French, and Simplified Chinese
 - User manuals also available at help.madrix.com
 - More information available at www.madrix.com
 - Can receive and process up to 512 DMX channels
 - Can transmit up to 512 DMX channels
 - Control via DMX via USB
 - Built with NEUTRIK connector
 - Made in Germany
- Package contents**
- 1 x device, 1 x user manual, 1 x CD, 1 x USB cable

Technical specifications:

Weight: 13,04 kg

EUROLITE LED PIX-8 QCL Bar

Power supply:	230 V AC, 50 Hz
Power consumption:	180,00 W
IP classification:	IP20
Control:	DMX
Preprogrammed in:	Light´J; LED PC-Control 512
Dimensions:	Length: 44,5 cm Depth: 13 cm Height: 16,5 cm
Weight:	3,2 kg
Beam angle:	21°
LED number:	8
LED type:	8 W QCL
DMX channels:	4/6/7/11/19/32/35
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Dimensions (L x W x H):	445 x 130 x 165 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

MADRIX NEO - USB DMX512 interface

Power supply:	5V DC 500 mA
Power connection:	Mains input via USB, type B power supply cord for USB A mains connection (provided)
DMX channels:	Input 512 Output 512
DMX output:	1 x 5-pin XLR (F) mounting version
Control:	DMX via USB
USB port:	USB 2.0, type B
Use of brands:	Built with NEUTRIK connector
Dimensions:	Width: 7,8 cm Depth: 5,9 cm Height: 3,5 cm
Weight:	0,24 kg