



Features:

FUTURELIGHT EYE-7.i LED Moving Head Beam

4in1 moving head beam with unlimited PAN and TILT movement

- Equipped with 7 x 15 W quadcolor LED with RGBW colors
- Compact housing
- Narrow illumination angle
- High PAN/TILT speed and Infinity function (.i) for unlimited PAN and TILT movement
- Exact positioning via 16 bit PAN/TILT movement resolution, dimmer intensity and colors
- Master dimmer
- Color presets
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices
- DMX control via every standard DMX controller
- 7 LEDs 15 W high-power 4in1 RGBW (homogenous color mix)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)

Logistic

- Beam effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
- Fixtures available for LED PC-Control 512
- With a beam angle of 7°

EUROLITE DMX Move Controller 512

Controller with color & motion effects (28 devices, 18 control channels each)

- DMX controller for DMX light effect units such as moving heads, scanners and LED spot lights with RGBW color mixture
- 512 DMX channels can be assigned and inverted as desired to 32 control channels (softpatch)
- For 28 fixtures with 18 control channels each
- USB port for storing program data
- Quick programming thanks to 9 integrated movement patterns and 7 color effects (PAN/TILT position, fade time and running time adjustable)
- Manual, time-controlled or sound-controlled chase running mode
- 2 DMX fixture levels can be controlled, each with up to 18 channels
- 16 DMX channel faders
- 2 jog wheels for pan/tilt
- Blackout function
- Can transmit up to 512 DMX channels
- (19") 48.3 cm rack installation 3 U
- Programmable 32 scenes/chases each with 600 cues
- Control via DMX; RDM
- Monochrome LCD display
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer
- Silent operation

Technical specifications:

Weight:	15.99 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

FUTURELIGHT EYE-7.i LED Moving Head Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110.00 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED type:	7 x 15 W high-power 4in1 RGBW (homogenous color mix)
Max. TILT movement:	Exact positioning (16 bit resolution) plus infinity auto position correction (feedback)
Max. PAN movement:	Exact positioning (16 bit resolution) plus infinity auto position correction (feedback)
Flash rate:	0 - 18 Hz

DMX channels:	14; 15; 16; 22
DMX input:	1 x 5-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
Fixtures available for:	LED PC-Control 512
Beam angle (1/2 peak):	7°
Beam angle (1/10 peak):	12°
Illuminance in Lux (lx):	Red (R) 3m: 2714 lx, 6m: 611 lx Green (G) 3m: 4900 lx, 6m: 1161 lx Blue (B) 3m: 830 lx, 6m: 199 lx Cold white (CW) 3m: 5539 lx, 6m: 1294 lx All 3m: 12673 lx, 6m: 2948 lx
Housing color:	Black
Dimensions:	Width: 24.4 cm Depth: 17.9 cm Height: 35 cm
Weight:	6.80 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE DMX Move Controller 512

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	2.70 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 32 scenes/chases each with 600 cues
DMX channels:	Output 512
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; RDM
Housing color:	Black
Display type:	Monochrome LCD display
Available storage media:	USB devices (FAT 32)
USB port:	Type A
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48.3 cm Depth: 13 cm Height: 8.9 cm
Weight:	2.39 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

2 x FUTURELIGHT EYE-7.i LED Moving Head Beam

1 x omega bracket

1 x EUROLITE DMX Move Controller 512

1 x controller

1 x user manual

1 x external mains adapter