



Features:

EUROLITE PAR-56 Spot Short with Cable sil

PAR-56 housing with silicone cable and open cable ends

- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong cable tension relief
- The device is cooled by passive convection cooling
- With mounting bracket
- For PAR 56
- For application areas such as: Stage; clubs/dancing school; decoration; restaurants, bars and hotels; theater; video and photography; advertisement/Shop window
- Silent operation

EUROLITE Raylight PAR-56,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-56 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

OMNILUX 230V/300W GY-9.5 180h

Studio-lamp for base GY9.5

Logistic

- One-sided base
- Dimmable
- Very high color rendering index (CRI)

Technical specifications:

Weight:	0.94 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE PAR-56 Spot Short with Cable sil

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 500 W
Protection class:	Protection class I
Suitable lamp:	Max. 230 V/500 W PAR-56
Power connection:	Fixed supply cord with open wires
Cable construction:	3 x 0.75 mm ² H05SS-F
Cable length:	Approx. 0.8 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame
Cooling:	Passive convection cooling
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	21.4 cm x 21.8 cm
Dimensions:	Length: 26 cm Width: 23.5 cm Height: 22 cm
Weight:	0.80 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	2 x Ø13mm
Material:	Metal, 2 mm
Diameter mounting holes:	4 x Ø8mm
Shape:	Octagonal
Grid size:	10 x 10 mm
Material:	Aluminum, 0.6 mm
Dimensions:	Length: 21.5 cm Width: 21.5 cm Diameter: Ø 17.1 cm
Material:	Steel, 4 mm
Color:	Silver
Special product:	Not designed for household room illumination

Intended use: Show effect lighting

EUROLITE Raylight PAR-56,GY-9.5 Socket long

Power supply:	230 V AC, 50 Hz
Power consumption:	500 W
Base:	GY9.5; GX16d
Beam angle (1/2 peak):	NSP
Color:	Alu colored
Dimensions:	Diameter: Ø 17.5 cm
Weight:	0.12 kg

OMNILUX 230V/300W GY-9.5 180h

Operating voltage:	230, 220 - 240 V
Nominal wattage:	300 W
Base:	GY9.5
Lamp type:	Incandescent lamp; halogen lamp
Lamp specification:	Dimmable
Beam angle:	310°
Color of light:	White
Color temperature:	2800K
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	Bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	180 h
Luminous flux:	3800 lm
Dimensions (LxD):	65x16 mm
Weight:	0.02 kg
Energy efficiency class (A - G):	G
EPREL-Nr:	1311455

Scope of delivery:

1 x spotlight
1 x filter frame
1 x lamp clamping ring
1 x user manual