




The article is no longer in our assortment.

Features:

EUROLITE STT-400/85 Winch Stand TÜV/GS

High-quality winch-stand, maximum load 85 kg, maximum height 400 cm

- 1-gear winch for easy lifting of the loads
- Automatic braking system
- Safety bolt for mechanical locking
- Easy handling
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height
- TÜV Süd certified
- For application areas such as: Mobile use

Package contents

- 1 x user manual

EUROLITE TAH-35M Truss Adapter, large

Adapter from 12 - 35 cm, maximum load WLL 300 kg

- Truss adapter for truss systems up to 55 mm diameter
- Adjustable clamps
- Adjustment between 120 mm and 350 mm
- LGA tested

Package contents

- 1 x adapter, 2 x bolt, 1 x user manual

ALUTRUSS TRILOCK 6082-2500 3-way Cross Beam

3-point truss system

Logistic

- Low weight
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x connection set

Technical specifications:

Weight:	72,60 kg
---------	----------

EUROLITE STT-400/85 Winch Stand TÜV/GS

Maximum carrying capacity:	85 kg
Minimum load:	25 kg
Standard:	DIN 15560-27, DIN EN ISO 12100-2
Height:	Maximum: 400 cm above 3 sections Minimum: 175 cm
Attachment system:	Ø 35mm
Steel rope:	Ø 4 mm
Type (general stands):	Light stand/wind up
Transport dimensions:	175 cm x 30 cm x 27 cm
Base area:	Ø 160 cm
Weight:	24,10 kg

EUROLITE TAH-35M Truss Adapter, large

Maximum load BGV C1 (8-fold):	150 kg
Maximum load WLL (4-fold):	300 kg
Attachment system:	Ø 35mm
Type (general stands):	Accessory
Material:	Steel
Width:	Maximum: 35 cm Minimum: 12 cm
Dimensions:	Width: 46 cm Depth: 7,50 cm Height: 22,50 cm
Weight:	2,40 kg

ALUTRUS TRILOCK 6082-2500 3-way Cross Beam

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding

Welding material:	AlMg 5
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 250 cm Width: 29 cm Height: 25,70 cm
Weight:	9,80 kg