

OMNITRONIC PM-4010 Pro DJ mixer

PRO 4+1-channel DJ mixer

Art. No.: 10006860

GTIN: 4026397380484



Features:

- 4 channels with gain control, 3-band equalizer, cue button, smooth and durable fader and 10-digit LED level meter
- 1 DJ microphone channel with 3-band equalizer, level control, on air and talkover selector
- Color illuminated rotary controls and rubber buttons
- Prefader listening to all input channels and the master output via adjustable headphones output, with cue mix/split function
- Replaceable crossfader with VCA technology for crossfading between input channels, with assignment switches, adjustable curve, reverse function and fader start function
- 2 separately controllable master channels with mono/stereo selector switch and balance control
- Master channel 1 with fader and 10-digit stereo LED level meter, switchable to master channel 2
- Master level switchable 0.75 V or 1.5 V
- Adjustable monitor output (DJ booth)
- 2 recording outputs, independent of the master and with on/off switch for DJ microphone signals
- Inputs: 10 x line (stereo RCA), additionally 1 x line at the front panel (stereo RCA/3.5 mm jack (1/8")); 2 x phono/line (stereo RCA), switchable; 1 x DJ microphone (XLR/6.3 mm jack), 2 x microphone (6.3 mm jack) and 1 x headphones (3.5 mm/6.3 mm jack (1/8"/1/4"))
- Outputs: 1 x master (stereo XLR/stereo RCA), 1 x master (6.3 mm stereo jack, bal.), booth (stereo RCA), 2 x record (stereo RCA) and 2 x fader start (3.5 mm jack (1/8"))
- Operation via supplied power unit

Logistic

EAN / GTIN: 4026397380484

Weight: 6,15 kg

Length: 0.47 m

Width: 0.39 m

Height: 0.17 m

Technical specifications:

Power consumption: 35.00 W

Frequency range: 20 - 20000 Hz

| | |
|-------------------------------|---|
| Dimensions: | Width: 32 cm Depth: 32 cm Height: 10 cm |
| Weight: | 5.55 kg |
| Power supply: | 230 V AC, 50 Hz, via supplied power unit |
| Inputs: | |
| DJ microphone: | combined XLR/6.3 mm jack (1/4") (bal.) |
| MIC 1, 2: | 6.3 mm jack (1/4") (bal.) |
| Minimum input voltage: | 1 mV RMS |
| LINE 1-10 (rear): | stereo RCA |
| LINE 8 (front): | stereo RCA/3.5 mm jack (1/8") |
| Minimum input voltage: | 150 mV RMS |
| PHONO 1, 2: | stereo RCA |
| Minimum input voltage: | 3 mV RMS |
| Outputs: | |
| MASTER 1: | stereo XLR/stereo RCA |
| Output voltage: | 0.75 V/1.5 V RMS (switchable) |
| MASTER 2: | 6.3 mm stereo jack |
| Output voltage: | 0.75 V/1.5 V RMS (switchable) |
| BOOTH: | stereo RCA |
| Output voltage: | 0.75 V |
| REC: | stereo RCA |
| Output voltage: | 0.75 V |
| Headphones output: | 3.5 mm/6.3 mm jack (1/8"/1/4") (min. 8 ohms) |
| X-FADER START: | 2 x 3.5 mm jack (1/8") |
| Tone control (DJ microphone): | |
| 1 x high: | -12 dB to +12 dB/ 10 kHz, ± 1 dB |
| 1 x middle: | -12 dB to +12 dB/ 1 kHz, ± 1 dB |
| 1 x low: | -12 dB to +12 dB/ 100 Hz, ± 1 dB |
| Talkover attenuation: | -15 dB |
| Tone control (channel 1-4): | |
| 4 x high: | -26 dB to +12 dB/ 10 kHz, ± 1 dB |
| 4 x middle: | -26 dB to +12 dB/ 1 kHz, ± 1 dB |
| 4 x low: | -26 dB to +12 dB/ 100 Hz, ± 1 dB |
| S/N ratio: | >75 dB |
| Distortion: | 0.03% |
| Dimensions (WxHxD): | 320 x 320 x 110 mm |

Scope of delivery: