

## OMNITRONIC RS-802 Recording mixer

Well-structured 8-channel studio and live mixer

Art. No.: 10040075

GTIN: 4026397183245



The article is no longer in our assortment.

### Features:

- Low-noise 8-channel mic/line mixer
- 4 mono inputs with XLR sockets, +48V phantom power and balanced line inputs
- 2 stereo inputs with balanced 6.3 mm jack sockets
- Stereo inputs can also be operated mono
- 3-band EQ for all inputs
- Peak LED per mono input
- Aux Send per channel for controlling external effectors
- Stereo Aux Return with balanced 6.3 mm jack sockets
- Separate Main Mix, Booth and headphones outputs
- Tape inputs assignable to Master, Booth/headphones
- Precise 10-fold stereo LED meter

### Logistic

EAN / GTIN: 4026397183245

Weight: 3,25 kg

Length: 0.37 m

Width: 0.31 m

Height: 0.12 m

### Technical specifications:

|                    |                                                  |
|--------------------|--------------------------------------------------|
| Power consumption: | 15,00 W                                          |
| Dimensions:        | Width: 27 cm<br>Depth: 25 cm<br>Height: 5,5 cm   |
| Weight:            | 2,75 kg                                          |
| Power supply:      | 2 x 20 V AC, 50/60 Hz<br>via included power unit |
| Inputs:            |                                                  |

|                         |                             |
|-------------------------|-----------------------------|
| 4 x mono                | XLR or balanced 6.3 mm jack |
| 2 x stereo              | balanced 6.3 mm jacks       |
| 1 x Aux Return:         | balanced 6.3 mm jacks       |
| 1 x Tape In             | stereo RCA                  |
| Outputs:                |                             |
| 1 x Master Out          | balanced 6.3 mm jacks       |
| 1 x Control Room        | balanced 6.3 mm jacks       |
| 1 x Aux Send:           | balanced 6.3 mm jacks       |
| 1 x Tape Out            | stereo RCA                  |
| Frequency range:        |                             |
| Microphone:             | 10-60000 Hz, $\pm 3$ dB     |
| Mono:                   | 10-60000 Hz, $\pm 3$ dB     |
| Stereo:                 | 10-55000 Hz, $\pm 3$ dB     |
| Distortion:             | 0.01 %                      |
| S/N ratio:              | 112 dB                      |
| Tone control/channel:   |                             |
| Treble:                 | $\pm 15$ dB at 12 kHz       |
| Middle:                 | $\pm 15$ dB at 2.5 kHz      |
| Bass:                   | $\pm 15$ dB at 80 Hz        |
| Dimensions (W x D x H): | 270 x 250 x 55 mm           |