

# OMNITRONIC LH-045 Microphone Preamplifier

1-channel microphone preamplifier

Art. No.: 10355045

GTIN: 4026397169102



## Features:

- 1 microphone, XLR (bal.) or 6.3 mm jack (unbal.)
- Variable gain control (6-50 dB)
- Phantom power can be switched on
- Clip LED
- 1 line output, XLR (bal.) or 6.3 mm (unbal.)
- For application areas such as: Installation; mobile use; mobile djs / entertainer

## Logistic

EAN / GTIN: 4026397169102

Weight: 0,71 kg

Length: 0.23 m

Width: 0.14 m

Height: 0.09 m

## Technical specifications:

Power supply:	230 V AC, 50 Hz 12V 150 mA
Pin configuration:	Inside - / outside +
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Number of channels:	1
Frequency range:	25 - 16000 Hz
S/N ratio:	>75 dB
THD:	<0.01 % at 1 kHz
Phantom power:	30 V DC

Impedance:	Input: 10 kOhm
Gain:	50 dB
Control elements:	Level control, phantom power switch
Connections:	Input: microphone via 1 x 3-pin XLR (F) mounting version Input: microphone via 1 x 6.3 mm plug (unbal.) Output: line via 1 x 3-pin XLR (M) mounting version Output: line via 1 x 6.3 mm plug (unbal.)
Max. level:	Input: +4 dB, bal. Input: +10 dB, unbal.
Material:	Metal
Color:	Silver
Dimensions:	Width: 11.7 cm Depth: 9.2 cm Height: 4 cm
Weight:	0.54 kg

### Scope of delivery:

1 x device  
1 x external mains adapter  
4 x foot  
1 x user manual