OMNITRONIC LH-061 PRO Dual DI Box passive

Passive 2-channel DI box/splitter, black

Art. No.: 10355061

GTIN: 4026397541762

Features:

- 2 high-impedance signal inputs via two 6.3 mm jacks
- 2 low-impedance XLR outputs
- Converts 2 separate unbalanced line inputs (e.g. CD player, instruments) into 2 balanced XLR outputs, for connecting a mixer
- Switchable input attenuation: 0 dB, -20 dB, -40 dB
- Cables can be routed under the housing
- For application areas such as: Installation; mobile use; mobile djs / entertainer

Logistic

EAN / GTIN: 4026397541762
Weight: 0,66 kg
Length: 0.14 m
Width: 0.12 m
Heigth: 0.07 m

Technical specifications:

Frequency range:	15 - 30000 Hz
Impedance:	Input: 50 kOhm Output: 600 Ohm
Input attenuation:	0 dB, -20 dB, -40 dB; switchable
Control elements:	Groundlift selector, Input sensitivity switch
Connections:	Input: 2 x 6.3 mm jack socket (mono) mounting version Output: line via 2 x 3-pin XLR Link: 2 x 6.3 mm jack socket (mono) mounting version
Max. level:	Output: +6 dBu

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Color:	Black
Dimensions:	Width: 13.3 cm Depth: 11.5 cm Height: 5.4 cm
Weight:	0.61 kg

Scope of delivery:

1 x user manual
1 x device

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.