

OMNITRONIC GEQ-215B Equalizer 2x15-band

2 x graphic equalizer 15-band

Art. No.: 10355521

GTIN: 4026397360370



Features:

- 2-channel version, 2 x 15 frequency controls with 2/3 octave steps
- Short sliding frequency controls with center click
- EQ gain switchable ± 6 dB to ± 15 dB
- Switchable low cut filter
- Separate level control per channel
- Bypass switch allows instant comparison of the original sound with the equalized sound
- 7-fold LED level meter with clip indicator
- Inputs and outputs via 6.3 mm jack sockets (1/4") and XLR sockets
- Groundlift switch
- Rack installation, 1 U

Logistic

EAN / GTIN: 4026397360370

Weight: 3,15 kg

Length: 0.55 m

Width: 0.25 m

Height: 0.08 m

Technical specifications:

| | |
|--------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 10.00 W |
| Equalizer: | 2 x graphic equalizer 15-band |
| Dimensions: | Width: 48.3 cm Depth: 17.5 cm Height: 4.45 cm |
| Weight: | 2.60 kg |
| Input impedance: | 10/20 kohms (unb./bal.) |

| | |
|-------------------------|---|
| Output impedance: | 300/150 kohms (unb./bal.) |
| In/Out connectors: | XLR, jack |
| S/N ratio: | >95 dB |
| Crosstalk: | >90 dB |
| Distortion: | <0.01 % |
| Frequency range: | 20-20000 Hz, ± 0.5 dB |
| Output level: | - ~ to +6 dB |
| Control range: | ± 6 dB or ± 15 dB |
| Frequencies: | 2 x 25/40/63/100/160/250/400/630 Hz, 1/1.6/2.5/4/6.3/10/16 kHz |
| Low Cut: | 30 Hz, -3 dB |
| Dimensions (W x D x H): | 483 x 175 x 44 mm |

Scope of delivery:
