

OMNITRONIC PSM-6.5A Studio monitors/pair

Active 2-way Nearfield-monitor

Art. No.: 11036473

GTIN: 4026397192667



Features:

- Balanced frequency range for uncolored playback
- For studio use, home recording or high-end playback in living rooms
- Magnetic shielding for use next to computer monitors etc.
- Ferrofluid-cooled tweeter for brilliant treble
- Two independent amplifiers for HF and LF
- Active 2-way crossover
- Bass-reflex system
- Gain control for adjusting the input signal
- Dip switches for adjusting the monitor to the environmental conditions
- Limiter, switchable for avoiding clipping
- Line signal connection via XLR/jack socket
- Rugged MDF wood housing
- Packed as a pair (2 pieces)

Logistic

EAN / GTIN: 4026397192667

Weight: 26,50 kg

Length: 0.62 m

Width: 0.04 m

Height: 0.52 m

Technical specifications:

Power supply: 115/230 V AC, 50/60 Hz

Power consumption: 115.00 W

Output power: Max. 85 W

Frequency range: 40 - 20000 Hz

Dimensions: Width: 41.5 cm
Depth: 24.5 cm

	Height: 28.5 cm
Weight:	24.50 kg
Amplifier power:	
HF:	30 W
LF:	85 W
Components:	16.5 cm woofer (6.5"), 2.5 cm tweeter (1")
Connection:	XLR/jack socket
Sensitivity:	90 dB
Crossover:	2.5 kHz
Total Harmonic Distortion:	0.05 %
Min. input sensitivity:	1 V
Input impedance:	10 kohms
Gain control:	-6/+9 dB
HF/MF-adjustment:	±2 dB @ 10-20 kHz
LF-adjustment:	±2 dB @ 20-80 Hz
Dimensions (H x W x D):	415 x 245 x 285 mm

Scope of delivery:
