

OMNITRONIC OD-6A Wall Speaker active white 2x

Active 2-way speaker pair with mount, 6.5" woofers and 40 W RMS

Art. No.: 11036929

GTIN: 4026397543698



Features:

- Dedicated PA speaker systems for fixed installations
- 2-way system with 16.5 cm woofer (6.5") and dome tweeter, magnetic shielding
- Class A/B circuitry: optimum sound and power at low weight and compact dimensions
- Separate controls for volume, high and low frequencies
- Each speaker system is equipped with an unbalanced RCA input and balanced spring terminals
- Additional 3.5 mm jack input, ideal for portable MP3 players
- Attractive plastic cabinet with metal grille
- Panning and tilting mounting bracket allows ceiling or wall installation in most varying angles
- Packed as a pair
- For indoor PA applications
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles

Logistic

EAN / GTIN: 4026397543698

Weight: 9,50 kg

Length: 0.50 m

Width: 0.23 m

Height: 0.33 m

Technical specifications:

| | |
|--------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with Euro plug (provided) |
| Power: | Program: 80W Rated: 40W RMS |
| Frequency range: | 80 - 20000 Hz |
| Attachment system: | Panning and tilting mounting bracket for ceiling or wall installation in most varying angles |

| | |
|-------------------|--|
| Speaker: | 1 x woofer 6.5" |
| Type of speaker: | On ceiling/on wall speaker |
| Color: | White |
| Dimensions: | Width: 19.5 cm Depth: 19.5 cm Height: 30 cm |
| Weight: | 8.90 kg |
| Circuitry: | class A/B |
| Components: | 16.5 cm woofer (6.5"), 2.5 cm tweeter (1") |
| Connection: | RCA, unbal. 3.5 mm jack, unbal. spring terminals, bal. |
| Sensitivity: | 89 dB |
| Maximum SPL: | 96 dB |
| Dispersion angle: | 170° x 170° |

Scope of delivery:
