

## OMNITRONIC ODP-204T Installation Speaker 100V white 2x

2 weather-proof 4" wall speakers (IP65) with mount, 40 W RMS

Art. No.: 11036953

GTIN: 4026397629712



**List price: 236.81 €**

incl. 19% VAT.

### Description:

Great sound - also runs with 100 volts

You want reliable and balanced sound for your bar, restaurant, shop or the conference area of your hotel? You need indoor and outdoor speakers? With the OPD series you get powerful installation speakers that meets all your requirements.

The speakers have a brilliant sound pattern and are available in a low ohm (16 ohms) and in a 100 V version. These two cover both small and large installations. A rotatable mounting bracket is included in the delivery. A swivel wall mount with matching colors is optionally available.

With their weatherproofed (IP65) plastic cabinet the ODP speakers are well prepared for outdoor use, indoor use is of course also possible.

### Logistic

EAN / GTIN: 4026397629712

Weight: 6,95 kg

Length: 0.42 m

Width: 0.20 m

Height: 0.30 m

### Features:

- 2-way system with 10 cm woofer (4") and 2 cm dome tweeter (0.8")
- Durable plastic cabinet with metal grille
- Power selector switch with 16 ohms operating position
- Screw plug terminal for easy handling
- With mounting bracket
- Suitable for outdoor use IP65
- 2 pieces per set
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

#### Package contents

- 1 x user manual, 2 x top, 2 x mounting bracket, 12 x screw, 2 x safety eyelet, 2 x lid, 4 x washer, 2 x screwing, 2 x screw plug-in terminal

## Technical specifications:

IP classification:	IP65
Power:	Program: 80W Rated: 40W RMS (100V PA) Rated: 40W RMS (16 Ohm)
Frequency range:	75 - 20000 Hz
Sensitivity:	88 dB (1W/1m)
Max. SPL:	103 dB
Dispersion angle:	120° x 90°
Impedance:	Public address systems 100V; 16 ohms
Attachment system:	Mounting bracket
Power tapping:	10W; 20W; 40W RMS via selector switch switchable
Control elements:	Level control
Connections:	Input: speaker via screw terminal
Crossover frequency:	3500 Hz
Speaker:	1 x woofer 4" Voice coil lows 1" 1 x dome tweeter 0,8" Voice coil calotte tweeter 0,8"
Type of speaker:	Compact cabinet speaker; on ceiling/on wall speaker
Color:	White
Dimensions:	Width: 14,1 cm Depth: 17 cm Height: 23 cm
Weight:	6,35 kg