

OMNITRONIC XFM-212AP Active 2-way Speaker Set with Wireless Microphone

Active speaker system set with audio player, Bluetooth and wireless microphone, 150 W RMS

Article No.: 11038759
GTIN: 4026397639681



Features:

- Set consists of one active speaker with integrated amplifier and one passive speaker
- For application areas such as: Mobile use; mobile djs / entertainer; sports centres/gyms
- <p>OMNITRONIC XFM-212AP Active 2-Way Speaker with Wireless Microphone
- 2-way bass-reflex systems with 30 cm woofer (12") and 3.4 cm tweeter (1.34")
- SD card slot and USB port
- UHF receiver unit and matching wireless microphone
- 1 mic input with separate level controls
- 1 line input XLR/6.3 mm jack) with separate level control
- Master control with 2-band EQ
- Control via IR remote control; Bluetooth
- UHF 863 - 865 MHz License-free and approved in Europe
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- For application areas such as: Mobile use; mobile djs / entertainer; sports centres/gyms
- <p>OMNITRONIC XFM-212 Passive 2-Way Speaker
- 2-way bass-reflex systems with 30 cm woofer (12") and 3.4 cm tweeter (1.34")
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- For application areas such as: Mobile use; mobile djs / entertainer; sports centres/gyms

Logistic

EAN / GTIN: 4026397639681
Weight: 22,45 kg
Length: 0.83 m
Width: 0.34 m
Height: 0.64 m

Technical specifications:

Weight: 21.40 kg

OMNITRONIC XFM-212AP Active 2-Way Speaker with Wireless Microphone

Power supply:	230 V AC, 50 Hz
Power consumption:	250 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Program: 250W Rated: 150W RMS
Frequency range:	50 - 18000 Hz
Sensitivity:	95 dB
Control:	IR remote control; Bluetooth
Audio player:	USB + SD + Bluetooth
Frequency band:	UHF 863 - 865 MHz
Carrier frequency:	865 MHz
Attachment system:	Flange: Ø 35mm
Controls:	Limiter
Status LED:	Power, clip
Connections:	Input: microphone via 1 x 3-pin XLR Input: microphone via 1 x 6.3 mm plug (unbal.) Input: line via 1 x 3-pin XLR Input: line via 1 x stereo RCA Output: line via 1 x 3-pin XLR Output: speaker via speaker built-in socket (F)
Equalizer:	Master: 1 x 2-band tone control
Speaker:	2 x woofer 12" 1 x tweeter 1.35"
Carrying handle:	3 pc/pcs
Material:	Plastic
Dimensions:	Width: 37.5 cm Depth: 31.5 cm Height: 58 cm
Weight:	12.10 kg

OMNITRONIC XFM-212 Passive 2-Way Speaker

Power:	Program: 250W Rated: 150W RMS
Frequency range:	50 - 18000 Hz
Sensitivity:	95 dB
Attachment system:	Flange: Ø 35mm
Connections:	Output: speaker via speaker built-in socket (F)
Speaker:	2 x woofer 12" 1 x tweeter 1.35"
Carrying handle:	3 pc/pcs

Material:	Plastic
Dimensions:	Width: 37.5 cm Depth: 31.5 cm Height: 58 cm
Weight:	9.30 kg

Scope of delivery:

1 x OMNITRONIC XFM-212AP Active 2-Way Speaker with Wireless Microphone

- 1 x remote control
- 1 x compact cabinet speaker
- 1 x user manual
- 1 x battery
- 1 x speaker cable
- 1 x power cord
- 1 x declaration of conformity
- 1 x microphone

1 x OMNITRONIC XFM-212 Passive 2-Way Speaker

- 1 x compact cabinet speaker