

## OMNITRONIC XKB-215A 2-way Speaker, active, DSP

Active speaker with 15" woofer, 1.75" driver, 60 W RMS HF, 300 W RMS LF

Art. No.: 11038796

GTIN: 4026397606492



### Features:

- Active PA speaker system for touring applications and permanent installations
- DSP-controlled biamp amplifier (LF class D, HF class A/B)
- 24-bit DSP with adjustable high-pass filter, parametric 3-band EQ and signal delay
- Built-in Bluetooth player for audio streaming from compatible Bluetooth devices such as smartphones, tablets and notebooks
- 2-way bass-reflex enclosure with 38 cm woofer and 4 cm titanium driver
- 2 mic/line inputs (XLR/6.3 mm jack) with separate level controls
- Digital signal processor
- DSP presets: LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL
- Control via Bluetooth
- LCD display
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- Application possibility: Standing; monitoring; on stand
- For application areas such as: Mobile use; rental; sports centres/gyms; mobile djs / entertainer

### Logistic

EAN / GTIN: 4026397606492

Weight: 22,55 kg

Length: 0.52 m

Width: 0.43 m

Height: 0.77 m

### Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 800 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

Power:	Program: 600W Rated: 60W RMS HF Rated: 300W RMS LF
Frequency range:	50 - 20000 Hz
Sensitivity:	96 dB
Max. SPL:	121 dB
DSP:	Digital signal processor
DSP presets:	LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL
Dispersion angle:	90° x 50°
Control:	Bluetooth
Attachment system:	Flange: Ø 35mm
Circuitry:	Class D Biamp
Display type:	LCD display
Control elements:	Encoder, Master control
Controls:	Limiter
Status LED:	Power, signal, limit
Connections:	Output: line via 1 x 3-pin XLR
Input channels:	2 x mono with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial
Equalizer:	Master: 1 x 3-band tone control
Speaker:	1 x woofer 15" Voice coil compression tweeter highs 1.75"
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Carrying handle:	3 pc/pcs
Dimensions:	Width: 37 cm Depth: 45 cm Height: 70 cm
Weight:	20.95 kg

### Scope of delivery:

1 x top  
1 x user manual  
1 x power cord  
1 x declaration of conformity