

OMNITRONIC COMPACT-100 1.1 Active system

Mobile and compact active PA system, 100 watts RMS

Art. No.: 11038830

GTIN: 4026397512939



Features:

- Mobile column PA system with top speaker and active subwoofer with class D circuitry
- Ultra-compact, extremely light - this system can be installed and setup in no time
- Ideal for DJs, entertainers, small bands and various kinds of mobile PA applications
- Dual class D amplifier (70 W + 30 W RMS)
- 25 cm subwoofer in bassreflex cabinet provides powerful, dry bass
- Top with 16.5 cm bass-midrange speakers and 2.5 cm driver system
- Passive 2-way crossover, PTC tweeter protection
- Balanced XLR/6.3 mm inputs and XLR parallel output
- Master and subwoofer level controls
- Lockable speaker connectors
- Complete protection set against short-circuit, overheat, overload and overcurrent
- Scratch-resistant lacquer surface and flange

Logistic

EAN / GTIN: 4026397512939

Weight: 31,90 kg

Length: 0.56 m

Width: 0.42 m

Height: 0.79 m

Bulky product

Technical specifications:

Power supply: 115/230 V AC, 50/60 Hz

Power consumption: 150.00 W

Dimensions: Width: 48.1 cm
Depth: 33.6 cm
Height: 39.1 cm

Power output sine:

Subwoofer: 70 W RMS

Satellite speakers:	30 W RMS
Components:	
Subwoofer:	25 cm woofer (10")
Satellite speakers:	16.5 cm woofer (6.5"), 2.5 cm tweeter (1")
Frequency range:	
Subwoofer:	45-140 Hz
Satellite speakers:	140-20000 Hz
Line input:	XLR/6.3 mm jack, bal.
Parallel output:	XLR
Protection circuits:	Short-circuit, overheat, overload, overcurrent
Dimensions (L x W x H):	
Subwoofer:	81 x 336 x 391 mm
Satellite speaker:	221 x 231 x 359 mm
Weight:	
Subwoofer:	19 kg
Satellite speaker:	6.6 kg

Scope of delivery:
