

OMNITRONIC COMBO-75 Active PA system

150 W portable combo PA system

Art. No.: 11038897













The article is no longer in our assortment.

Features:

- Portable PA system for mobile use, ideal for rental companies
- Two 150 W speakers
- Low-noise 4-channel mic/line mixer and amplifier integrated into a wooden housing with black plastic cover, handle and speaker-flange for installation on a speaker-stand or wall-mounting
- Amplifier output power 2 x 75 W RMS / 4 ohms
- 4 bal. mono input channels (XLR and 6.3 mm jack) with gain control, 2-band EQ and digital reverb
- 1 adjustable line input (stereo RCA) e.g. CD and MP3 players or for multimedia applications from PC and laptop
- Adjustable effect way for controlling external effect units (aux send/return)
- Master section with level control, 2-band EQ and reverb control
- 2 systems can be interconnected for stereo operation

Logistic

EAN / GTIN: 4026397431605

Weight: 6,75 kg Length: 0.47 m Width: 0.28 m Heigth: 0.18 m

Technical specifications:

| Power supply: | 115/230 V AC, 50/60 Hz |
|--------------------|------------------------|
| Power consumption: | 300,00 W |
| Frequency range: | 30 - 20000 Hz |
| Dimensions: | Width: 47,5 cm |
| | Depth: 31,5 cm |
| | Height: 32,5 cm |
| Weight: | 17,70 kg |

| Mixer unit: | |
|-----------------------|---|
| Dimensions: | 480 x 255 x 135 mm |
| Inputs: | 4 x mono mic/line (XLR/6.3 mm jack, bal.) |
| | 1 x line (stereo RCA) |
| | 1 x aux return (6.3 mm jack, bal.) |
| Outputs: | 1 x aux send (6.3 mm jack, bal.) |
| | 2 x speaker out (Speaker) |
| Amplifier unit: | |
| Nominal power output: | 2 x 75 W RMS / 4 ohms |
| Maximum power output: | 2 x 150 W / 4 ohms |
| Distortion: | 0.85 % |
| S/N ratio: | >90 dB |
| Loudspeakers: | |
| Rated power: | 100 W RMS |
| Program power: | 150 W |
| Components: | 25 cm woofer (10"), 2 cm horn (0.8") |
| Sensitivity: | 93 dB |
| Impedance: | 8 ohms |

530 x 370 x 277 mm

Dimensions: