


## OMNITRONIC PAS-215A MK3 2-Way Top, active, DSP

Active 15" PA speaker with DSP presets, 2 input channels, 550 W RMS

Art. No.: 11039483

GTIN: 4026397669978



**The article is no longer in our assortment.**

### Features:

- Active PA speaker system for touring applications and permanent installations
- 2-way bass-reflex enclosure with 38 cm woofer and 2.5 cm compression driver
- DSP-controlled class D amplifier with 550 watts power
- Switchable low cut (120 Hz, 90 Hz)
- 1 adjustable line input via XLR/6.3mm combo jack and RCA
- 1 adjustable mic/line input via XLR/6.3mm combo jack
- XLR output for linking further active speaker systems, switchable CH 1/CH 2
- Optimized for combination with PAS subwoofers
- Digital signal processor
- DSP presets: FLAT; DJ; MONITOR
- Dual flange
- With rigging points
- Black metal grille with acoustic foam
- 2 Rugged carrying handles
- Application possibility: Standing; suspended; monitoring; on stand
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; rental

#### Package contents

- 1 x user manual, 1 x power cord, 1 x compact cabinet speaker

### Logistic

EAN / GTIN: 4026397669978

Weight: 28,10 kg

Length: 0.50 m

Width: 0.49 m

Height: 0.77 m

### Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 650 W

Output power:	550 W RMS
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	50 - 20000 Hz
Max. SPL:	127 dB
DSP:	Digital signal processor
DSP presets:	FLAT; DJ; MONITOR
Dispersion angle:	90° x 60°
Attachment system:	Dual flange: Ø 35mm (0°/5°)
Flying points:	4 x M10 thread; 6 x M8 thread
Circuitry:	Class D
Controls:	Power on/off transient; limiter
Status LED:	DSP presets
Connections:	Input: 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: 1 x stereo RCA Link: 3-pin XLR
Input channels:	1 x mono with mic-line switch via XLR or RCA, channel control via rotary dial 1 x mono with mic-line switch via XLR, channel control via rotary dial
Speaker:	1 x compression tweeter highs 1" with ferrit magnet Basket material: aluminum Voice coil compression tweeter highs 1,5" Horn vent 1" 1 x woofer 15" Voice coil lows 3"
Type of speaker:	Compact cabinet speaker
Carrying handle:	2 pc/pcs
Material:	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 45 cm Depth: 69,5 cm Height: 43,5 cm
Weight:	26,30 kg