


PSSO K-215CM 2-Way Coaxial Wedge 400W

PRO PA speaker, 15" woofer, 1.4" horn, 400 W RMS / 8 ohms

Art. No.: 11041119

GTIN: 4026397516340

**The article is no longer in our assortment.****Features:**

- Rugged 2-way coaxial wedge, qualified for touring applications
- Housing made of 15 mm birch plywood
- 38 cm (15") bass speaker with diecast aluminum basket
- 36 mm horn tweeter (2.8", 72 mm voice coil)
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Premium passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Applications: standing, on a subwoofer or speaker stand, suspended, and as sidefill
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- European engineering

Logistic

EAN / GTIN: 4026397516340

Weight: 28,05 kg

Length: 0.57 m

Width: 0.42 m

Height: 0.65 m

Technical specifications:

| | |
|------------------|----------------------------------|
| Power: | Program: 800W Rated: 400W RMS |
| Frequency range: | 58 - 19000 Hz |
| Sensitivity: | 99 dB |
| Max. SPL: | 131 dB |

| | |
|----------------------|---|
| Dispersion angle: | 70° x 70° |
| Impedance: | 8 ohms |
| Connections: | Speaker via 2 x 2-pin SpeakON mounting version (F) |
| Crossover frequency: | 1500 Hz |
| Speaker: | 1 x woofer 15" 1 x horn 1" |
| Type of speaker: | Compact cabinet speaker; coaxial speaker; stage monitor |
| Use of brands: | CELTO ACOUSTIQUE driver Built with NEUTRIK connector |
| Dimensions: | Width: 58 cm Depth: 50,2 cm Height: 35,2 cm |
| Weight: | 25,50 kg |