

CELTO iFIX10 G2 2-way Coaxial Speaker natural/white

Passive speaker with 10" woofer, 1" driver and 600 W

Art. No.: 11043572

GTIN:



Features:

- Real 300 W power handling with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- High efficiency for incredible SPL to size ratio
- HF compression driver with ketone polymere dome
- With mounting bracket
- CELTO ACOUSTIQUE driver
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

Logistic

Technical specifications:

Power:	Peak: 1200W Program: 600W Rated: 300W AES
Frequency range:	95 - 22000 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	128 dB
Dispersion angle:	80° conical
Impedance:	8 ohms
Attachment system:	Mounting bracket

Connections:	Input: speaker via screw plug-in terminal
Crossover frequency:	Passive 1500 Hz Recommended In subwoofer combination High-pass 90-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 10" with ferrit magnet Basket material: aluminum Voice coil lows 2.5" 1 x annular compression driver 1" Voice coil annular 1.75" Diaphragmmaterial: PEEK (H.T. polymer)
Type of speaker:	On ceiling/on wall speaker; coaxial speaker
Type of construction:	Closed Box
Use of brands:	CELTO ACOUSTIQUE driver
Material:	Birch multiplex, 15 mm, CNC made with tongue and grove assembly
Color:	Nature, painted
Dimensions:	Width: 30 cm Depth: 30.4 cm Height: 30 cm
Weight:	12 kg

Scope of delivery:

- 1 x top
- 1 x mounting bracket
- 1 x nut
- 8 x washer
- 1 x safety eyelet
- 2 x screw
- 1 x screw plug-in terminal