

CELTO ACOUSTIQUE PM15 G2 2-Way Fullrange Loudspeaker

True full-range loudspeaker, for fixed installation via 9 M8 flying points

Art. No.: 11043682

GTIN:



The article is no longer in our assortment.

Features:

- Horn 90 degree rotatable for horizontal or vertical use
- Complies with DIN 18032-3 (Ball-proof)

Package contents

- 1 x top

Logistic

Technical specifications:

Power:	Program: 1400W Rated: 700W RMS
Frequency range:	38 - 22000 Hz
Sensitivity:	98 dB (1W/1m)
Max. SPL:	133 dB
Dispersion angle:	80° x 50° rotatable horn
Impedance:	8 ohms
Standard:	DIN 18032-3 (Ball-proof),
Connections:	Input: speaker via 2 x speaker built-in socket (F)
Crossover frequency:	Passive 1400 Hz, 12db/oct on LF Passive 1400 Hz, 18db/oct on HF Recommended 35 Hz, 24db/oct in full-range mode

	60-140 Hz with subwoofer
Speaker:	1 x woofer 13,5" with ferrit magnet Basket material: aluminum Voice coil lows 3,5" Diaphragmmaterial: PEEK (H.T. polymer) 1 x annular compression driver 1" with ferrit magnet Voice coil annular 1,75"
Type of speaker:	Compact cabinet speaker
Type of construction:	Transmission line
Material:	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 41,0 cm Depth: 45,0 cm Height: 72,0 cm
Weight:	34,00 kg