

## CELTO PM15 G3 2-way Fullrange Loudspeaker

Passive speaker with 15" woofer, 1" driver and 1600 W

Art. No.: 11043684

GTIN:



**List price: on demand €**

incl. 19% VAT.

### Features:

- Horn 90 degree rotatable for horizontal or vertical use
- Complies with DIN 18032-3 (Ball-proof)
- Dual flange
- With rigging points
- Built with NEUTRIK connector
- CELTO ACOUSTIQUE driver
- For application areas such as: Theater; music school; concerts/FoH's; restaurants, bars and hotels; sports centres/gyms; architecture; multi-purpose hall

### Logistic

### Technical specifications:

Power:	Peak: 3200W Program: 1600W Rated: 800W AES
Frequency range:	38 - 22000 Hz
Sensitivity:	98 dB (1W/1m)
Max. SPL:	133 dB
Dispersion angle:	80° x 50° rotatable horn
Impedance:	8 ohms
Standard:	DIN 18032-3 (Ball-proof),
Attachment system:	Dual flange: Ø 35mm (0° / 10°)

Flying points:	9 x M8 thread
Connections:	Speaker via 2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	Passive 1400 Hz Recommended 35 Hz, 24db/oct in full-range mode 60-140 Hz with subwoofer
Speaker:	1 x woofer 15" with ferrit magnet Basket material: aluminum Voice coil woofer in/out wound 3.5" 1 x annular compression driver 1" with ferrit magnet Voice coil annular 1.75" Diaphragmmaterial: PEEK (H.T. polymer)
Type of speaker:	Compact cabinet speaker
Type of construction:	Transmission line
Use of brands:	Built with NEUTRIK connector CELTO ACOUSTIQUE driver
Material:	Birch multiplex, CNC made with tongue and grove assembly
Color:	Black, textured coating, painted
Dimensions:	Width: 41.0 cm Depth: 45.0 cm Height: 72.0 cm
Weight:	30.65 kg

### Scope of delivery:

1 x top