

CELTO ACOUSTIQUE IWAC118S Subwoofer

Subwoofer with integrated rigging system, lightweight design

Art. No.: 11043705













List price: on demand €

incl. 19% VAT.

Features: Logistic

- Real 1200 W RMS power capacity
- Premium 18" Neodymium driver with ±11mm linear Xmax
- Triple-forced cooling system for low power compression
- Heavy braced cabinet for vibration free dynamic response
- Fully integrated rigging & stacking system
- Touring-grade textured coating finish
- For application areas such as: Theater; concerts/FoH's; sports centres/gyms; stage; rental Package contents
- 1 x bass

Technical specifications:

5	D. J. 4000M	
Power:	Peak: 4800W	
	Program: 2400W	
	Rated: 1200W RMS	
Frequency range:	33 - 100 Hz	
Sensitivity:	97 dB (1W/1m)	
Max. SPL:	133 dB	
Dispersion angle:	Omnidirectional	
Impedance:	4 ohms	
Attachment system:	M20 thread	

Flying points:	With integrate rigging system
Connections:	Speaker via 3 x 4-pol SpeakON mounting version (F)
Crossover frequency:	Active mode only
	Recommended
	High-pass 30 Hz, 24db/oct
	Low-pass 70-120 Hz when used with IWAC210
Speaker:	1 x tweeter 18" with neodymium magnet with dual demodulating rings
	Basket material: aluminum
	Voice coil woofer in/out wound 4"
Material:	Baltic birch plywood, 18 mm, CNC made with tongue and grove assembly
Color:	Black, matte
Dimensions:	Width: 70 cm
	Depth: 51,8 cm
	Height: 74,5 cm
Weight:	58,00 kg