

CELTO SP48 Digital Speaker Controller

Art. No.: 11043814

GTIN: 4026397688238



The article is no longer in our assortment.

Features:

- Digital signal processor
- Sample rate: 96 kHz
- (19") 48.3 cm rack installation
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397688238
 Weight: 3,20 kg
 Length: 0.55 m
 Width: 0.30 m
 Height: 0.10 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 35 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	20 - 20000 Hz
THD:	<0.003 % at 1 kHz
Network connection:	Protocol: Ethernet TCP/IP via
DSP:	Digital signal processor
Impedance:	Input: 40 kOhm Output: 60 Ohm
Gain:	Input: -40 dB to +6 dB Output: -40 dB to +15 dB

Filter:	Linkwitz-Riley; Butterworth; Bessel; 12db/oct; 18db/oct; 24db/oct; 48db/Okt
Delay:	0 - 1000 ms
Dynamic range:	Input: 112 dB Output: 118 dB
Sample rate:	96 kHz
Connections:	Input: line via 4 x 3-pin XLR Output: line via 8 x 3-pin XLR
Crossover frequency:	20-20000 Hz
Max. level:	Input: +18 dBu Output: +20 dBu
USB port:	Type B
Housing design:	(19") 48.3 cm rack installation
Dimensions:	Width: 48.3 cm Depth: 20 cm Height: 4.4 cm
Weight:	2.72 kg

Scope of delivery:

- 1 x controller
- 1 x power cord
- 1 x USB cable
- 1 x network cable
- 4 x foot
- 1 x CD