

INTUSONIC SPA22 Mounting Remote Power Station

Flush-mount PSU for the INTUPAK VAA22 mixing panel

Art. No.: 12604196

GTIN: 5060502923561



Description:

The INTUPAK SPA22 addresses the simple yet decisive question of how to power wall-mounted devices. With a plethora of wall-mounted preamplifiers, amplifiers and wireless receiver panels in the market, most manufacturers count on the installers' ability to hide a wall wart in a drywall or run a long low-voltage cable from a remote location. Intusonic however delivers the smarter answer in the shape of a sleek and flexible PSU, fitting just into wall box sizes with minimal depth (86 mm) offering flush or surface mount options like other Intusonic wall-mounted products.

With its symmetrical $\pm 12V$ low-noise DC output, it provides the groundwork for great, high-headroom audio quality. And with terminal strip outputs plus IntuLink in-line RJ45 connections with data throughput and power refresh, it can power both stand-alone preamp products like the VAA22 or provide long-distance power beyond a zoner's on-board supply abilities to IntuGrid wall panels.

Features:

- Flush mounting
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 3 W

Protection class: Protection class I

Logistic

EAN / GTIN: 5060502923561

Weight: 0,29 kg

Length: 0.10 m

Width: 0.10 m

Height: 0.09 m

| | |
|---------------------|--|
| Power connection: | Mains input via screw terminal |
| Network connection: | RJ-45 (F) mounting version |
| Housing color: | Black matte |
| Housing design: | Flush mounting |
| Dimensions: | Width: 8.6 cm Depth: 5.8 cm Height: 8.6 cm |
| Weight: | 0.24 kg |

Scope of delivery:

1 x device
1 x user manual