

## OMNITRONIC BR-115 Pocket receiver set

Multifrequency pocket receiver set

Art. No.: 13062000

GTIN: 4026397139754



**The article is no longer in our assortment.**

### Features:

- Set includes multifrequency receiver and mini ear phones
- Can be used for in-ear applications
- 16 UHF frequencies (800.100-813.000 MHz) via DIP switches selectable
- LED display for power supply
- Level control
- Audio output via 3.5 mm mono jack socket for mono earphones
- Power supply via 2 x 1.5 V mignon batteries (type AA) (not supplied)
- A wireless microphone or a belt transmitter with lavalier microphone or headset microphone can be ordered separately

### Logistic

EAN / GTIN: 4026397139754

Weight: 0,22 kg

Length: 0.21 m

Width: 0.07 m

Height: 0.06 m

### Technical specifications:

|                    |                                                                                                                                                                                                     |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions:        | Width: 7 cm<br>Depth: 2,5 cm<br>Height: 10,6 cm                                                                                                                                                     |
| Antenna:           | Detachable                                                                                                                                                                                          |
| System:            | Non-diversity, one channel                                                                                                                                                                          |
| Carrier frequency: | UHF 800.100-813.000 MHz (16 ch.)<br><br>800.875, 801.375, 802.375, 803.125, 803.875,<br>804.500, 805.125, 805.875, 806.625, 807.375,<br>807.875, 808.375, 809.125, 810.250, 810.875,<br>811.875 MHz |

|                         |                              |
|-------------------------|------------------------------|
| Frequency stability:    | ±0.005 %                     |
| T.H.D.:                 | <1 % at 1 kHz                |
| Tone signal:            | 32.768 kHz                   |
| S/N-ratio:              | >94 dB at 48 kHz deviation   |
| Input sensitivity:      | 8 dB                         |
| Selectivity:            | >50 dB                       |
| Dynamic range:          | >96 dB                       |
| Modulation method:      | FM-frequency modulation      |
| Coverage:               | >30 m (with line-of-sight)   |
| Frequency range:        | 50-15000 Hz (±3 dB)          |
| Audio output:           | 3.5 mm mono jack socket      |
| Power supply:           | 2 mignon batteries (type AA) |
| Current consumption:    | approx. 110 mA               |
| Battery life:           | max. 12 hours                |
| Dimensions (L x W x H): | 106 x 70 x 25 mm             |
| Weight:                 | 100 g                        |