

## OMNITRONIC UHF-204 Wireless Mic System 823-832MHz

Complete 4-channel UHF PLL microphone system

Art. No.: 13063236

GTIN: 4026397533644



The article is no longer in our assortment.

### Features:

- 4-channel receiver unit and 4 hand-held microphones with UHF PLL technology
- Operation in the Duplex Gap 823-832 MHz
- Diversity system with two removable antennas (TNC connection)
- 4 separate channels with volume controls and LEDs for power supply, carrier signal and audio signal
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output
- Jack cable included
- Microphones with mute switch and color caps for distinction on stage
- Matching pocket transmitters can be ordered separately
- Receiver unit in a rugged metal housing
- Removable antennas (TNC connection)
- Incl. mounting brackets for 483 mm rack installation
- License-free in Germany and 13 other EU countries

#### Package contents

- 1 x microphone

### Logistic

EAN / GTIN: 4026397533644

Weight: 4,60 kg

Length: 0.53 m

Width: 0.30 m

Height: 0.12 m

### Technical specifications:

Frequency range: 40 - 18000 Hz

Dimensions: Width: 42 cm  
Depth: 22 cm  
Height: 5 cm

|                    |                                                                          |
|--------------------|--------------------------------------------------------------------------|
| Battery:           | 8 x Mignon (AA) (not included)                                           |
| System:            | Diversity, 4 channels                                                    |
| Carrier frequency: | 823.100 MHz, 824.925 MHz,<br>828.250 MHz, 830.900 MHz                    |
| Coverage:          | 50 m (with line-of-sight)                                                |
| RF power output:   | 10 mW                                                                    |
| Modulation method: | F3E                                                                      |
| S/N ratio:         | >105 dB                                                                  |
| Selectivity:       | >80 dB                                                                   |
| T.H.D.:            | <0.5 % at 1 kHz                                                          |
| Audio outputs:     | 400 mV, 2.2 kohms (XLR, bal.)<br>200 mV, 2.2 kohms (6.3 mm jack, unbal.) |
| Power supply:      |                                                                          |
| Receiver:          | 100-240 V AC, 50/60 Hz via supplied power unit                           |
| Power consumption: | 10 W                                                                     |
| Dimensions, weight |                                                                          |
| Receiver:          | 420 x 220 x 50 mm (L x W x H), 3 kg                                      |
| Microphones:       | 50 x 265 mm (D x L), 280 g                                               |