

OMNITRONIC UHF E-FLEX 2, Wireless Mic System 823-832/863-865 MHz Art. No.: 13063370

License-free 2-channel microphone system (UHF 863 - 865 MHz, UHF 823 - 832 MHz) with auto sync, incl. rack fit GTIN: 4026397740226



List price: 117.81 €

incl. 19% VAT.

Features:

- 2-channel receiver and 2 hand-held microphones with UHF PLL technology
- Quick and easy frequency adjustment at hand-held transmitter
- 16 selectable UHF frequencies (823-832 and 863-865 MHz)
- 2 separate channels with volume controls
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output
- Detachable BNC antennas
- Operating range up to 30m with line-of-sight
- UHF 863 - 865 MHz License-free and approved in Europe
- UHF 823 - 832 MHz License-free and approved in large parts of Europe

receiver

- Multicolor 4 digit 7-segment LED display
- Desktop console housing
- (19") 48.3 cm rack installation possible

microphone

- Polar pattern: Cardioid
- Multicolor 4 digit 7-segment LED display
- Charge status indicator

Package contents

- 1 x receiver, 1 x external mains adapter, 2 x antenna, 2 x microphone, 1 x jack cable, 2 x mounting bracket, 6 x screw, 4 x foot, 1 x user manual, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397740226

Weight: 2,25 kg

Length: 0.41 m

Width: 0.30 m

Height: 0.07 m

Technical specifications:

Type:	Wireless set
Protection class:	Protection class III
Number of channels:	2
Frequency range:	50 - 15000 Hz
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 863 - 865 MHz; UHF 823 - 832 MHz
Modulation:	FM
Frequency selection:	16 switchable frequencies In 2 groups
Weight:	1,87 kg
Receiver	
Power supply:	100-240 V AC, 50/60 Hz 12V DC 500 mA
Power consumption:	Max. 3,1 W
Power connection:	Mains input via coaxial power connector (M) power supply cord with AC unit (provided)
S/N ratio:	>90 dB
THD:	<0,05 % at 1 kHz
Housing color:	Black
Display type:	Multicolor 4 digit 7-segment LED display
Display:	Mute; channel , frequency , AF audio level , RF signal level
Control elements:	Power switch, level control per channel
Connections:	Input: antenna via 2 x BNC (F) Output: microphone via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR (M) mounting version
Material:	Metal
Housing design:	Desktop console housing (19") 48.3 cm rack installation possible
Mounting depth:	18,5 cm
Dimensions:	Width: 21,1 cm Depth: 14,4 cm Height: 4,2 cm
Weight:	0,970 kg
Microphone	
Type:	Hand-held transmitter
Power supply:	3V DC
Capsule type:	Dynamic
Polar pattern:	Cardioid
Battery:	Mignon (AA) (not included)
Sensitivity:	-54 dB
RF power output:	10 mW
Housing color:	Black

Display type:	Multicolor 4 digit 7-segment LED display
Display:	Frequency , channel , charge status indicator , Mute
Switch:	On/off/mute switch
Material:	Metal
Dimensions:	Length: 24,3 cm Diameter: Ø 5,5 cm
Weight:	0,27 kg