

OMNITRONIC WAMS-65BT Wireless PA System

Portable 6.5" PA with wireless microphone, audio player, Bluetooth and 40 W peak power

Art. No.: 13107003

GTIN: 4026397603590



Features:

- Portable all-in-one PA system with 40 watts output power
- 4-channel mixer
- 2-way bass-reflex system
- SD card slot and USB port
- 1 microphone input (XLR) with adjustable reverb effect
- UHF receiver unit and matching wireless microphone
- Power-efficient and battery-saving class D amplifier
- Tone control and master control
- Integrated automatic charging of the battery
- The device is cooled by passive convection cooling
- UHF 863 - 865 MHz License-free and approved in Europe
- Black metal grille
- Rugged carrying handle
- For application areas such as: Theater; mobile use; wedding/gala/events; product presentations and lectures

battery pack

- Battery pack must be ordered separately
- Cordless, flexible and versatile
- Battery operation up to 4h

audio player

- Control via Bluetooth; IR remote control
- Bluetooth: operating range up to 10m
- 2.4 GHz license-free worldwide
- 4 digit 7-segment LED display

microphone

- Polar pattern: Cardioid

Logistic

EAN / GTIN: 4026397603590

Weight: 4,80 kg

Length: 0.44 m

Width: 0.27 m

Height: 0.27 m

- Operating range up to 30m
remote control
- Operating range up to 10m

Technical specifications:

| | |
|-----------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz Or 12V DC |
| Power consumption: | 60 W |
| Protection class: | Protection class I |
| Output power: | 40 W RMS |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Battery/battery pack (not included) |
| Frequency range: | 62 - 18000 Hz |
| THD: | <0.5 % at 1 kHz |
| Cooling: | Passive convection cooling |
| Frequency band: | UHF 863 - 865 MHz |
| Carrier frequency: | 865 MHz |
| Frequency stability: | ± 0.005 % |
| Frequency selection: | Fixed frequencies |
| Housing color: | Black |
| Attachment system: | Flange: Ø 35mm |
| Circuitry: | Class D |
| Control elements: | Echo effect control, audio player |
| Status LED: | Power, peak, ON AIR, signal, charge status indicator |
| Connections: | Input: microphone via 1 x 3-pin XLR Input: line via 1 x stereo RCA Output: line via 1 x 6.3 mm plug (unbal.) |
| Channels: | Microphone channel: 1 x mono via XLR, channel control via rotary dial Input channel: 1 x stereo via RCA, channel control via rotary dial Input channel: 1 x stereo via audio player, channel control via rotary dial Input channel: 1 x mono via radio, channel control via rotary dial Master output: 1 x mono, channel control via rotary dial, tone control EQ |
| Speaker: | 1 x woofer 6.5" 1 x tweeter 1" |
| Type of speaker: | Compact cabinet speaker; wireless PA system |
| Type of construction: | Vented |
| Carrying handle: | 1 pc/pcs |
| Material: | ABS Acrylonitrile butadiene styrene |
| Color: | Black |
| Dimensions: | Width: 23.5 cm |

| | |
|--------------------------|---|
| | Depth: 22 cm Height: 35 cm |
| Weight: | 4.15 kg |
| Power supply: | 3V DC |
| Power connection: | Battery/battery pack |
| Capsule type: | Dynamic |
| Polar pattern: | Cardioid |
| Battery: | 2 x Mignon (AA) (not included) |
| Range: | Range up to 30m |
| RF power output: | 10 mW |
| Modulation: | FM |
| Switch: | On/off/mute switch |
| Material: | Plastic |
| Dimensions: | Length: 26 cm Diameter: Ø 4 cm |
| Weight: | 0.115 kg |
| Control: | Bluetooth; IR remote control |
| Bluetooth device name: | Omnitronic |
| Audio player: | USB + SD + Bluetooth |
| Range: | Bluetooth: range up to 10m |
| Frequency band: | 2.4 GHz |
| Display type: | 4 digit 7-segment LED display |
| Music format: | MP3, WAV |
| Available storage media: | USB devices/SD cards max. 32GB (FAT 32) |
| Power supply: | 3V DC |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Range: | Range up to 10m |
| Battery pack type: | 1 x lead 12 V, 2900 mAh, |
| Battery pack: | Battery operation up to 4h Recharging time 4h |

Scope of delivery:

- 1 x device
- 1 x power cord
- 1 x microphone
- 1 x remote control
- 1 x user manual
- 1 x declaration of conformity