



The article is no longer in our assortment.

Features:

EUROLITE LED TMH-15 Moving Head Zoom Wash

4in1 moving head wash with zoom and 15 W QCL LEDs

- Equipped with seven 15 W quadcolor LEDs with RGBW colors
- Compact lightweight
- Motorized zoom with 11° - 55° beam angle
- Color presets
- Positioning within 630° PAN and 200° TILT
- Stepless RGBW color mixture
- Masterdimmer
- Internal programs
- Strobe effect with 1-18 flashes per second
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-control via built-in microphone
- Control board with graphic LC display for adjusting the DMX-starting address, PAN/TILT reverse, program, reset
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- The device is cooled by cooling fan
- Control via DMX; stand-alone
- Preprogrammed in Light J; LED PC-Control 512
- Flicker-free
- With a beam angle of 11° - 55°

Logistic

ROADINGER Flightcase 4x TMH-15 with wheels

Trunk case with castors

- Fitted for 4 devices and accessory
- Additional accessory compartment
- Interior upholstered with foam
- High-quality workmanship with birch multiplex, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, big steel ball corners
- Lid with 2 tip-over locks
- 4 chrome butterfly locks
- 4 chrome case handles
- 4 castors (100 mm), 2 of which with locking brakes
- 4 stacking dishes for stacking the cases
- Castors
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	44,60 kg
---------	----------

EUROLITE LED TMH-15 Moving Head Zoom Wash

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
IP classification:	IP20
Lamp type:	LED lamp
Cooling:	Cooling fan
Control:	DMX; stand-alone
Preprogrammed in:	Light´J; LED PC-Control 512
Projection:	Flicker-free
Beam angle:	11° - 55°
Beam angle (1/2 peak):	11 - 28°
Beam angle (1/10 peak):	25 - 55°
Illuminance in Lux (lx):	Narrow red (R) 3m: 702 lx, 6m: 182 lx Narrow green (G) 3m: 1131 lx, 6m: 298 lx Narrow blue (B) 3m: 185 lx, 6m: 50 lx Narrow cold white (CW) 3m: 1139 lx, 6m: 304 lx Narrow all 3m: 2272 lx, 6m: 600 lx Wide red (R) 3m: 157 lx, 6m: 42 lx Wide green (G) 3m: 238 lx, 6m: 65 lx Wide blue (B) 3m: 54 lx, 6m: 15 lx Wide cold white (CW) 3m: 329 lx, 6m: 91 lx Wide all 3m: 562 lx, 6m: 155 lx
Housing color:	Black
Dimensions:	Width: 25 cm Depth: 15 cm Height: 33,5 cm
Weight:	5,35 kg

DMX channels:	13
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	18 Hz
LED type:	Cree 15 W QCL
LED number:	7
Maximum PAN-movement:	630°
Maximum TILT-movement:	200°
Beam angle:	11° - 28°
Dimensions (L x W x H):	150 x 250 x 335 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x TMH-15 with wheels

Maximum load:	100 kg
Transport aid:	Castors
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Dimensions:	Width: 76 cm Depth: 61,5 cm Height: 42 cm
Weight:	23,20 kg
Strength:	7 mm
Outside dimensions (W x D x H):	760 x 615 x 420 mm
Compartment dimensions (W x D x H):	125 x 280 x 300 mm
Accessory compartment (W x D x H):	100 x 610 x 320 mm