

## EUROLITE Set 4x LED THA-250F + Case

4x Theater-Spot with fresnel spot including PRO flightcase

Art. No.: 20000162

GTIN: 4026397586220



### Features:

- Very high color rendering index (CRI)
- With a beam angle of 5° - 38°
- Zoom motor driven; focus manual
- Flicker-free
- Control via RDM; stand-alone; DMX; quick select potentiometer for brightness and Zoom
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- 1 LED 200 W COB (chip-on-board) warm white (WW)
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Suspended; on stand
- <p>ROADINGER Flightcase 4x THA-250F with wheels
- <h2 class="featureSatz">Trunk case with castors, PRO version</h2>With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover

### Logistic

EAN / GTIN: 4026397586220

Weight: 70,00 kg

Length: 0.80 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 81.30 kg

---

### EUROLITE LED THA-250F Theater Spot

|                              |   |
|------------------------------|---|
| Power supply:                | 100-240 V AC, 50/60 Hz  |
| Power consumption:           | 265 W   |
| Protection class:            | Protection class I  |
| Power connection:            | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output:                | 1 x PowerCON (gray), mounting version   |
| Device fuse:                 | 5 x 20 mm, T 3 A fuse replaceable   |
| Lamp type:                   | LED lamp  |
| LED type:                    | 1 x 200 W COB (chip-on-board) warm white (WW)   |
| Flash rate:                  | 1.5 - 12 Hz   |
| Equipment:                   | Zoom motor driven; focus manual   |
| DMX channels:                | 3   |
| DMX input:                   | 1 x 3-pin XLR (M) mounting version<br>1 x 5-pin XLR (M) mounting version                        |
| DMX output:                  | 1 x 3-pin XLR (F) mounting version<br>1 x 5-pin XLR (F) mounting version                        |
| Cooling:                     | Temperature-controlled fan  |
| Control:                     | RDM; stand-alone; DMX; quick select potentiometer for brightness and Zoom                       |
| Fixtures available for:      | LED PC-Control 512; Light Captain; Light´J  |
| Projection:                  | Flicker-free  |
| PWM frequency:               | 3600 Hz   |
| Beam angle:                  | 5° - 38°  |
| Beam angle (1/2 peak):       | 5 - 28°   |
| Beam angle (1/10 peak):      | 12 - 38°  |
| Color temperature:           | 2800K   |
| Color rendering index (CRI): | 92 Ra   |
| Housing color:               | Black   |
| Attachment system:           | Mounting bracket  |
| Display type:                | LCD display   |
| Transport aid:               | Rubber feet   |
| Dimensions:                  | Length: 45.7 cm<br>Width: 33.6 cm<br>Height: 39.9 cm  |

|                       |  |
|-----------------------|--|
| Weight:               | 10.00 kg                                     |
| Noise classification: | Class 2 (slight noise)                       |
| Special product:      | Not designed for household room illumination |
| Intended use:         | Show effect lighting                         |

#### **ROADINGER Flightcase 4x THA-250F with wheels**

|                          |   |
|--------------------------|---|
| Maximum load:            | 100 kg  |
| Aluminum profile frames: | 25 mm   |
| Case handle:             | 4 pc/pcs  |
| Stop hinge:              | 3 pc/pcs  |
| Lock:                    | Butterfly lock: 2 pc/pcs  |
| Transport aid:           | 4 x castors with 2 locking brakes<br>4 x built-in stacking trays in the cover |
| Use of brands:           | Branded hardware  |
| Material:                | Birch multiplex, 7 mm   |
| Color:                   | Dark brown, laminated   |
| Accessory compartment:   | 11 cm x 81 cm x 30 cm   |
| Device compartment:      | 49.5 cm x 20 cm x 27 cm   |
| Inside dimensions:       | 110 cm x 81 cm x 30 cm  |
| Dimensions:              | Width: 116 cm<br>Depth: 86 cm<br>Height: 55 cm                                |
| Weight:                  | 32.60 kg  |

#### **Scope of delivery:**

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x barndoor
- 1 x filter frame