

EUROLITE Set 2x LED THA-40PC bk + Case

2x fanless Pc spot including PRO flightcase

Art. No.: 20000164

GTIN:



List price: 1034.11 €

incl. 19% VAT.

Features:

EUROLITE LED THA-40PC Theater Spot bk

Fanless PC spot (DMX), warm white 57 W LED, color rendering index (CRI) >90

- 1 powerful LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Preprogrammed in LED PC-Control 512; Light´J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 11° - 48°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rubber feet
- Silent operation
- For application areas such as: Trade fair and shop fitting; installation; stage; theater
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x barn door, 1 x filter frame, 1 x user manual

Logistic

ROADINGER Flightcase 2x THA-40 PC

Trunk case, PRO version

- With accessory compartment

- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

| | |
|---------|----------|
| Weight: | 15,85 kg |
|---------|----------|

EUROLITE LED THA-40PC Theater Spot bk

| | |
|------------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 40 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Fuse: | 5 x 20 mm, T 1 A fuse replaceable |
| LED type: | 1 x 57 W COB (chip-on-board) warm white (WW) |
| DMX channels: | 1; 2 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX |
| Preprogrammed in: | LED PC-Control 512; Light´J; Light Captain; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 11° - 48° |
| Beam angle (1/2 peak): | 11 - 37° |
| Beam angle (1/10 peak): | 17 - 48° |
| Color temperature: | 3100K |
| Color rendering index (CRI): | 91 Ra |
| Illuminance in Lux (lx): | Narrow 3m: 1656 lx, 6m: 424 lx Wide 3m: 348 lx, 6m: 103 lx |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | LCD display |
| Transport aid: | Rubber feet |
| Material: | Aluminum casting |
| Slot for spot length: | 13,1 cm x 13,1 cm |
| Dimensions: | Length: 27,5 cm |

| | |
|--------------------------|--|
| | Width: 20,5 cm Depth: 25 cm |
| Weight: | 3,85 kg |
| Noise classification: | Class 0 (no noise at all) |
| Mounting bracket | |
| Diameter mounting holes: | 1 x Ø10mm; 2 x Ø6mm |
| Material: | Metal, 3 mm |
| Power cord | |
| Cable construction: | 3 x 0,75 mm² H05VV-F |
| Cable length: | Approx. 1 m |
| Barndoor | |
| Material: | Aluminum, 1,5 mm; metal |
| Ring diameter: | Outside: 12,9 mm Inside: 10,9 mm |
| Filter frame | |
| Diameter mounting holes: | 1 x Ø4mm |
| Shape: | Octagonal |
| Material: | Aluminum, 0,8 mm |
| Dimensions: | Width: 13 cm Height: 13 cm Diameter: Ø 10,5 cm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 2x THA-40 PC

| | |
|--------------------------|---|
| Maximum load: | 50 kg |
| Aluminum profile frames: | 25 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Device compartment: | 16 cm x 31 cm x 12 cm |
| Accessory compartment: | 10,5 cm x 31 cm x 18 cm |
| Inside dimensions: | 60 cm x 31 cm x 20 cm |
| Dimensions: | Width: 64,5 cm Depth: 35 cm Height: 29 cm |
| Weight: | 8,15 kg |