

EUROLITE Set 2x LED THA-40PC bk + Case

2x fanless Pc spot including PRO flightcase

Art. No.: 20000164

GTIN: 4026397586244



Features:

- Very high color rendering index (CRI)
- Silent operation
- Control via stand-alone; DMX
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- 1 LED 57 W COB (chip-on-board) warm white (WW)
- Strobe effect
- Flicker-free
- The device is cooled by passive convection cooling
- With mounting bracket
- For application areas such as: Stage; decoration; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; video and photography; advertisement/Shop window; theater
- Application possibility: Suspended; on stand
- <p>ROADINGER Flightcase 2x THA-40 PC
- <h2 class="featureSatz">Trunk case, PRO version</h2>With accessory compartment
- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397586244

Weight: 15,85 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

Technical specifications:

Weight: 16.85 kg

EUROLITE LED THA-40PC Theater Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 57 W COB (chip-on-board) warm white (WW)
DMX channels:	1; 2
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Fixtures available for:	LED PC-Control 512; Light J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	11 - 37°
Beam angle (1/10 peak):	17 - 48°
Color temperature:	3100K
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Narrow 3m: 1656 lx, 6m: 424 lx Wide 3m: 348 lx, 6m: 103 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	13.1 cm x 13.1 cm
Dimensions:	Length: 27.5 cm Width: 20.5 cm Depth: 25 cm
Weight:	3.85 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø10mm; 2 x Ø6mm
Material:	Metal, 3 mm
Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1 m

Material:	Aluminum, 1.5 mm; metal
Ring diameter:	Outside: 12.9 mm Inside: 10.9 mm
Diameter mounting holes:	1 x Ø4mm
Shape:	Octagonal
Material:	Aluminum, 0.8 mm
Dimensions:	Width: 13 cm Height: 13 cm Diameter: Ø 10.5 cm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x THA-40 PC

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	16 cm x 31 cm x 12 cm
Accessory compartment:	10.5 cm x 31 cm x 18 cm
Inside dimensions:	60 cm x 31 cm x 20 cm
Dimensions:	Width: 64.5 cm Depth: 35 cm Height: 29 cm
Weight:	8.15 kg

Scope of delivery:

- 1 x spotlight
- 1 x barndoor
- 1 x filter frame
- 1 x user manual