

EUROLITE Set 4x AKKU UP-4 QCL Spot QuickDMX + Case with charging function 00000180

4x bright uplight wit 4 x 8 W 4in1 LEDs including PRO flightcase with charging function GTIN:



The article is no longer in our assortment.

Features:

EUROLITE AKKU UP-4 QCL Spot QuickDMX

Bright Uplight with 4 x 8 W 4in1 LED and QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 9,5h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 powerful LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone
- Preprogrammed in Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Flicker-free
- With a beam angle of 22°
- With bracket for floor use
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing

Package contents

- 1 x spotlight, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control, 1 x battery

Logistic

ROADINGER Flightcase 4x AKKU UP-4 QuickDMX with charging function

Trunk case with castors

- With 4 device compartments
- With accessory compartment
- High-quality workmanship with plywood multi-layer glued 8 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x case, 1 x user manual, 1 x power cord

Technical specifications:

EUROLITE AKKU UP-4 QCL Spot QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1 m
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh
Battery pack:	Battery operation up to 9,5h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone
Preprogrammed in:	Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	32°

Housing color:	Black
Attachment system:	Bracket for floor use
Dimensions:	Width: 16,7 cm Depth: 13,8 cm Height: 18,8 cm
Weight:	3,59 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU UP-4 QuickDMX with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 5 A fuse replaceable
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Material:	Plywood multi-layer glued, 8 mm
Color:	Black, laminated
Device compartment:	18 cm x 19,5 cm x 17 cm
Accessory compartment:	9,5 cm x 41 cm x 17 cm
Inside dimensions:	49,5 cm x 41 cm x 17 cm
Dimensions:	Width: 62 cm Depth: 46 cm Height: 40,5 cm
Weight:	14,65 kg