



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED TSL-1200 Scan

Scanner with 120 W LED, gobos, rotating prism, color wheel, motorized focus

- Equipped with a 120 W COB LED
- 13 or 15 DMX channel mode selectable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Internal programs
- Color wheel with 8 dichroic color filters and white
- Rainbow effect with adjustable speed
- Gobo-wheel with 7 rotating gobos plus open
- Gobo shake function
- Rotating 3-facet prism
- Exact positioning via 16 bit PAN/TILT movement resolution
- Strobe effect with adjustable speed
- Motorized focus
- Electronic dimmer
- Lightbeam with 14° radiation angle
- Control board with graphic LC display and four operating buttons for adjusting the DMX starting address, PAN/TILT reverse
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- 1 powerful LED 120 W COB (chip-on-board) cold white (CW)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven
- Gobo effect
- Color wheel with 8 dichroic filters plus open

### Logistic

- Gobo wheel with rotating gobos, 7 gobos and open
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 14°

## ROADINGER Flightcase 2x TSL-750/TSL-1200

### Trunk case

- With 2 device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- Rugged carrying handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Made in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 30,40 kg |
|---------|----------|

## EUROLITE LED TSL-1200 Scan

|                     |                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------|
| Power supply:       | 100-240 V AC, 50/60 Hz                                                                           |
| Power consumption:  | 165 W                                                                                            |
| IP classification:  | IP20                                                                                             |
| Power connection:   | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Lamp type:          | LED lamp                                                                                         |
| LED type:           | 1 x 120 W COB (chip-on-board) cold white (CW)                                                    |
| Max. TILT movement: | 80° exact positioning (16 bit resolution)                                                        |
| Max. PAN movement:  | 175° exact positioning (16 bit resolution)                                                       |
| Flash rate:         | 0 - 18 Hz                                                                                        |
| Equipment:          | Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven                                 |
| Color generation:   | Color wheel with 8 dichroic filters plus open                                                    |
| Gobos:              | Gobo wheel with rotating gobos, 7 gobos and open                                                 |
| DMX channels:       | 13; 15                                                                                           |
| DMX input:          | 1 x 3-pin XLR (M) mounting version<br>1 x 3-pin XLR (M) mounting version                         |
| DMX output:         | 1 x 3-pin XLR (F) mounting version<br>1 x 3-pin XLR (F) mounting version                         |
| Cooling:            | Cooling fan                                                                                      |
| Control:            | DMX; stand-alone; sound to light via microphone                                                  |

|                        |                                                   |
|------------------------|---------------------------------------------------|
| Preprogrammed in:      | Light J; LED PC-Control 512; Light Captain        |
| Projection:            | Flicker-free                                      |
| Beam angle:            | 14°                                               |
| Beam angle (1/2 peak): | 14°                                               |
| Housing color:         | Black                                             |
| Dimensions:            | Width: 26 cm<br>Depth: 47,5 cm<br>Height: 22,5 cm |
| Weight:                | 8,45 kg                                           |
| Special product:       | Not designed for household room illumination      |
| Intended use:          | Show effect lighting                              |

#### **ROADINGER Flightcase 2x TSL-750/TSL-1200**

|                          |                                                   |
|--------------------------|---------------------------------------------------|
| Maximum load:            | 50 kg                                             |
| Aluminum profile frames: | 30 mm                                             |
| Case handle:             | 2 pc/pcs                                          |
| Carrying handle:         | 1 pc/pcs                                          |
| Stop hinge:              | 2 pc/pcs                                          |
| Lock:                    | Butterfly lock: 2 pc/pcs                          |
| Material:                | Birch multiplex, 7 mm                             |
| Color:                   | Dark brown, laminated                             |
| Device compartment:      | 23 cm x 27 cm x 46 cm                             |
| Middle compartment:      | 10,5 cm x 29 cm x 46 cm                           |
| Inside dimensions:       | 64 cm x 29 cm x 46 cm                             |
| Dimensions:              | Width: 68,5 cm<br>Depth: 33,5 cm<br>Height: 57 cm |
| Weight:                  | 13,50 kg                                          |