

EUROLITE Set 4x AKKU UP-4 QCL Spot QuickDMX + Case

4 uplights with battery, without cable, in flightcase

Art. No.: 2000277

GTIN:



Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 9.5h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone
- Flicker-free
- With a beam angle of 22°
- With bracket for floor use
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing
- <p>ROADINGER Flightcase 4x AKKU UP 4 QCL Spot QuickDMX
- <h2 class="featureSatz">Carrying case, PRO version</h2>Cable bushing allows loading the devices inside
- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges

Logistic

- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 20.56 kg

EUROLITE AKKU UP-4 QCL Spot QuickDMX

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 50 W |
| Protection class: | Protection class I |
| Power connection: | Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Cable length: | Approx. 1 m |
| Power output: | 1 x P-Con (gray), mounting version |
| Battery pack type: | 1 x lithium ion 14.8 V, 7800 mAh, 115.44 Wh |
| Battery pack: | Battery operation up to 9.5h depending on program used Recharging time 3h |
| Lamp type: | LED lamp |
| LED type: | 4 x 8 W SMD 9080 4in1 RGBW (homogenous color mix) |
| DMX channels: | 3; 4; 6; 8; 10 |
| DMX input: | 1 x 3-pin XLR (M) mounting version IP |
| DMX output: | 1 x 3-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone |
| Fixtures available for: | Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Projection: | Flicker-free |
| Carrier frequency: | 2.4 GHz |
| Beam angle (1/2 peak): | 22° |
| Beam angle (1/10 peak): | 32° |
| Housing color: | Black |
| Attachment system: | Bracket for floor use |
| Dimensions: | Width: 16.7 cm Depth: 13.8 cm Height: 18.8 cm |
| Weight: | 3.59 kg |

| | |
|-----------------------|---|
| Noise classification: | Class 0 (no noise at all) |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x AKKU UP 4 QCL Spot QuickDMX

| | |
|--------------------------|---|
| Maximum load: | 25 kg |
| Aluminum profile frames: | 25 mm |
| Case handle: | 1 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 1 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Device compartment: | 14.5 cm x 15.5 cm x 12 cm |
| Inside dimensions: | 44 cm x 35 cm x 19.5 cm |
| Accessory compartment: | 10 cm x 35 cm x 17 cm |
| Dimensions: | Width: 48.5 cm Depth: 39.5 cm Height: 26 cm |
| Weight: | 6.20 kg |

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x declaration of conformity
- 1 x power cord
- 1 x remote control
- 1 x battery