



Features:

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With mounting bracket
- For PAR 30
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- <p>OMNILUX PAR-30 230V SMD 11W E-27 LED 6500K
- <h2 class="featureSatz">PAR-30 LED lamp</h2>Easy lamp replacement
- Energy-saving
- Hot restrike
- Easy installation
- Good color rendering index (CRI)

Logistic

EAN / GTIN: 4026397472158
Weight: 0,80 kg
Length: 0.30 m
Width: 0.22 m
Heigth: 0.21 m

Technical specifications:

Weight: 0.70 kg

Energy efficiency class (A - G): F

EUROLITE PAR-30 Spot silver

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 100 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0.4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-30
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	12.8 cm x 12.8 cm
Dimensions:	Length: 23.5 cm Width: 14.5 cm Height: 21 cm
Weight:	0.47 kg
Noise classification:	Class 0 (no noise at all)
Material:	Aluminum
Material:	Aluminum
Dimensions:	Length: 12.6 cm Width: 12.6 cm Diameter: Ø 9.4 cm
Weight:	0.018 kg

OMNILUX PAR-30 230V SMD 11W E-27 LED 6500K

Voltage (lamps):	230 V, AC
Nominal wattage:	11 W
Base:	E27
Lamp type:	LED lamp
Lamp specification:	Hot restrike
Beam angle:	50°
Setup:	Easy installation
Color of light:	White
Color temperature:	6500K
Color rendering index (CRI):	83 Ra
Lead time:	0.2 s
Construction:	PAR-30

Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	20000 h
Luminous flux:	850 lm
Wavelength:	600 nm
Lamp current:	0.087 A
Dimensions (LxD):	92x95 mm
Weight:	0.19 kg
Energy efficiency class (A - G):	F
EPREL-Nr:	1016879

Scope of delivery:

1 x EUROLITE PAR-30 Spot silver

- 1 x spotlight
- 1 x filter frame
- 1 x user manual

1 x OMNILUX PAR-30 230V SMD 11W E-27 LED 6500K

- 1 x illuminant