



**The article is no longer in our assortment.**

### Features:

#### EUROLITE PAR-16 Spot MR-16 silver

PAR-16 housing with GX-5.3 socket for 12 V MR-16 lamp

- Mini spots for 50 mm cool beam lamps
- Detailed original reconstruction of the big stage spots
- Ideal for decoration purposes
- Control via plug and play
- For PAR 16

#### Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

### Logistic

#### OMNILUX MR-16 12V GX-5,3 5W LED COB 3000K

Cool-beam mirrored lamp

- Different illumination angles for different application areas
- Low power consumption
- Powerful LED illuminant with COB (Chip on Board) technology
- A homogenous light blend is thereby guaranteed
- Comfortable warm white light
- Hot restrike
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

|         |         |
|---------|---------|
| Weight: | 0,23 kg |
|---------|---------|

---

### EUROLITE PAR-16 Spot MR-16 silver

|                          |                                                       |
|--------------------------|-------------------------------------------------------|
| Power supply:            | 12V AC                                                |
| Power consumption:       | Max. 50 W                                             |
| IP classification:       | IP20                                                  |
| Protection class:        | Protection class III                                  |
| Power connection:        | Fixed supply cord with open wires                     |
| Cable length:            | Approx. 0,25 m                                        |
| Base:                    | GX5.3                                                 |
| Lamp type:               | Selectable                                            |
| Color generation:        | Via color filter frame                                |
| Control:                 | Plug and play                                         |
| Housing color:           | Silver                                                |
| Material:                | Aluminum, 1 mm                                        |
| Slot for spot length:    | 8 cm x 8 cm                                           |
| Dimensions:              | Length: 17 cm<br>Width: 11 cm<br>Height: 13 cm        |
| Weight:                  | 0,19 kg                                               |
| Diameter mounting holes: | 2 x Ø10mm                                             |
| Material:                | Aluminum, 3 mm                                        |
| Material:                | Aluminum                                              |
| Dimensions:              | Length: 7,8 cm<br>Width: 7,8 cm<br>Diameter: Ø 5,3 cm |
| Weight:                  | 0,01 kg                                               |

### OMNILUX MR-16 12V GX-5,3 5W LED COB 3000K

|                     |                                                        |
|---------------------|--------------------------------------------------------|
| Voltage (lamps):    | 12 V, AC                                               |
| Nominal wattage:    | 5 W                                                    |
| Base:               | GX5.3                                                  |
| Lamp type:          | LED lamp; clear lamp; low voltage lamp; cool Beam lamp |
| Lamp specification: | Hot restrike                                           |
| Beam angle:         | 36°                                                    |
| Color of light:     | White                                                  |
| Color temperature:  | 3000K                                                  |
| Lead time:          | 1 s                                                    |

|                                    |                          |
|------------------------------------|--------------------------|
| Construction:                      | MR-16; reflector; bi pin |
| Operating temperature max.:        | 40° C                    |
| Operating temperature min.:        | 20° C                    |
| Burning position:                  | S180 (universal)         |
| Lamp life:                         | 30000 h                  |
| Luminous flux:                     | 350 lm                   |
| Wavelength:                        | 592 nm                   |
| Lamp current:                      | 0,72 A                   |
| Dimensions (LxD):                  | 65x48 mm                 |
| Energy efficiency class (A++ - E): | A+                       |