



The article is no longer in our assortment.

Features:

EUROLITE PAR-16 Spot MR-16 white

PAR-16 housing with GX-5.3 socket for 12 V MR-16 lamp

- Mini spots for 50 mm cool beam lamps
- Detailed original reconstruction of the big stage spots
- Ideal for decoration purposes
- Control via plug and play
- For PAR 16

Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

Logistic

OMNILUX MR-16 12V GX-5,3 5W LED COB 6400K

Cool-beam mirrored lamp

- Different illumination angles for different application areas
- Low power consumption
- Powerful LED illuminant with COB (Chip on Board) technology
- A homogenous light blend is thereby guaranteed
- Comfortable and fresh, white light
- Hot restrike
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	0,25 kg
---------	---------

EUROLITE PAR-16 Spot MR-16 white

Power supply:	12V AC
Power consumption:	Max. 50 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0,25 m
Base:	GX5.3
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Housing color:	White
Material:	Aluminum
Slot for spot length:	8 cm x 8 cm
Dimensions:	Length: 17 cm Width: 11 cm Height: 13 cm
Weight:	0,21 kg
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Material:	Aluminum
Dimensions:	Length: 7,8 cm Width: 7,8 cm Diameter: Ø 5,3 cm
Weight:	0,01 kg

OMNILUX MR-16 12V GX-5,3 5W LED COB 6400K

Voltage (lamps):	12 V, AC
Nominal wattage:	5 W
Base:	GX5.3
Lamp type:	LED lamp; clear lamp; low voltage lamp; cool Beam lamp
Lamp specification:	Hot restrike
Beam angle:	36°
Color of light:	White
Color temperature:	6400K
Lead time:	1 s

Construction:	MR-16; reflector; bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	30000 h
Luminous flux:	380 lm
Lamp current:	0,43 A
Dimensions (LxD):	65x51 mm
Weight:	0,04 kg
Energy efficiency class (A++ - E):	A+