

## EUROLITE Set 4x LED PAR-56 QCL Short bk + EPS Case

4x PAR-56 Spot with 9 x 8 W 4in1 LED and RGBW color mixing including flightcase

Art. No.: 2000323

GTIN: 4026397603088



### Features:

- 9 LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Control via stand-alone; DMX; IR remote control; sound to light via microphone
- Fixtures available for Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 8°
- With mounting bracket
- 4 digit 7-segment LED display
- Available in various colors
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Suspended; on stand
- <p>ROADINGER Flightcase EPS-56 4x PAR-56 Spot short
- <h2 class="featureSatz">Trunk case</h2>With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

EAN / GTIN: 4026397603088

Weight: 17,84 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

## Technical specifications:

---

Weight: 14.55 kg

---

### EUROLITE LED PAR-56 QCL Short bk

|                         |   |
|-------------------------|---|
| Power supply:           | 100-240 V AC, 50/60 Hz  |
| Power consumption:      | 50 W  |
| IP classification:      | IP20  |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)  |
| Lamp type:              | LED lamp  |
| LED type:               | 9 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)   |
| DMX channels:           | 4; 6; 8   |
| DMX input:              | 3-pin XLR (M) mounting version  |
| DMX output:             | 3-pin XLR (F) mounting version  |
| Control:                | Stand-alone; DMX; IR remote control; sound to light via microphone  |
| Fixtures available for: | Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection:             | Flicker-free  |
| Beam angle:             | 8°  |
| Beam angle (1/2 peak):  | 8°  |
| Beam angle (1/10 peak): | 25°   |
| Housing color:          | Black   |
| Attachment system:      | Mounting bracket  |
| Display type:           | 4 digit 7-segment LED display   |
| Dimensions:             | Width: 20.5 cm<br>Depth: 17.5 cm<br>Height: 23 cm   |
| Weight:                 | 1.65 kg   |
| Photobiological safety: | Risk Group 0  |
| Battery:                | 1 x button cell 3.0 V CR2025 lithium manganese built-in   |
| Special product:        | Not designed for household room illumination  |
| Intended use:           | Show effect lighting  |

### ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Maximum load: 25 kg

---

|                          |   |
|--------------------------|---|
| Aluminum profile frames: | 30 mm   |
| Case handle:             | 2 pc/pcs  |
| Stop hinge:              | 2 pc/pcs  |
| Lock:                    | Butterfly lock: 1 pc/pcs                          |
| Material:                | Birch multiplex, 7 mm                             |
| Color:                   | Dark brown, laminated                             |
| Compartment dimensions:  | 22 cm x 22 cm x 24 cm                             |
| Inside dimensions:       | 44 cm x 44 cm x 24 cm                             |
| Dimensions:              | Width: 48.5 cm<br>Depth: 48.5 cm<br>Height: 31 cm |
| Weight:                  | 7.95 kg   |

### **Scope of delivery:**

---

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery