

OMNITRONIC Set 2x XKB-215A + 2x MagiCarpet-181A

Art. No.: 20000419

GTIN:



The article is no longer in our assortment.

Features:

OMNITRONIC XKB-215A 2-way Speaker, active, DSP

Active speaker with 15" woofer, 1,75" driver, 60 W RMS HF, 300 W RMS LF

- Active PA speaker system for touring applications and permanent installations
- DSP-controlled biamp amplifier (LF class D, HF class A/B)
- 24-bit DSP with adjustable high-pass filter, parametric 3-band EQ and signal delay
- Built-in Bluetooth player for audio streaming from compatible Bluetooth devices such as smartphones, tablets and notebooks
- 2-way bass-reflex enclosure with 38 cm woofer and 4 cm titanium driver
- 2 mic/line inputs (XLR/6.3 mm jack) with separate level controls
- Digital signal processor
- DSP presets: LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL
- Control via Bluetooth
- LCD display
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- Application possibility: Standing; monitoring; on stand
- For application areas such as: Mobile use; rental; sports centres/gyms; mobile djs / entertainer

Package contents

- 1 x top, 1 x user manual, 1 x power cord, 1 x declaration of conformity

OMNITRONIC MagiCarpet-181A MK2 Active Subwoofer

Active 18" PA bassreflex subwoofer, 500 W

- Active bassreflex subwoofer with 250 W RMS power
- 45 cm bass speaker (18") with 100 mm voice coil

Logistic

- Adjustable XLR input with feed-through output
- XLR output with high-pass filter for active top speakers
- Adjustable crossover frequency from 40 to 250 Hz
- Bass boost, ground lift and phase control
- Power and signal/limit indicator
- Rugged wooden housing with black felt cover
- Metal flange for mounting top speakers
- Bar handles for easy transport
- Impact-resistant metal grille, steel corners and support feet
- For mobile applications and permanent installations
- Suitable for car transport

OMNITRONIC Distance Tube Subwoofer/Satellite 100cm

Distance tube

- Connecting tube for satellite systems
- For stand inserts with standard diameter (35 mm)
- Powder-coated steel version

OMNITRONIC Speaker cable XLR 2x1.5 3m bk

Speaker cable

- Suitable for all passive speaker-systems with XLR socket
- 1.5 mm² thick cores for amplified signals without signal loss
- Not to be used as microphone cable!

OMNITRONIC XLR Cable 3-pin 10m bk

Audio cable with 3-pin XLR connectors<p class="attributgroup">Package contents

- 1 x XLR cable

Technical specifications:

OMNITRONIC XKB-215A 2-way Speaker, active, DSP

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 800 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Program: 600W Rated: 60W RMS HF Rated: 300W RMS LF
Frequency range:	50 - 20000 Hz
Sensitivity:	96 dB
Max. SPL:	121 dB
DSP:	Digital signal processor
DSP presets:	LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL
Dispersion angle:	90° x 50°
Control:	Bluetooth
Attachment system:	Flange: Ø 35mm
Circuitry:	Class D Biamp
Display type:	LCD display
Control elements:	Encoder, Master control

Controls:	Limiter
Status LED:	Power, signal, limit
Connections:	Output: line via 1 x 3-pin XLR
Input channels:	2 x mono with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial
Equalizer:	Master: 1 x 3-band tone control
Speaker:	1 x woofer 15" Voice coil compression tweeter highs 1,75"
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Carrying handle:	3 pc/pcs
Dimensions:	Width: 37 cm Depth: 45 cm Height: 70 cm
Weight:	20,95 kg

OMNITRONIC MagiCarpet-181A MK2 Active Subwoofer

Power supply:	230 V AC, 50 Hz
Power consumption:	280 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Program: 500W Rated: 250W RMS
Frequency range:	33 - 250 Hz
Max. SPL:	126 dB
Attachment system:	Ø 35mm
Connections:	Input: line via 2 x 3-pin XLR Link: line via 2 x 3-pin XLR Output: high-pass via 2 x 3-pin XLR
Speaker:	1 x woofer 18"
Type of speaker:	Subwoofer
Type of construction:	Vented
Dimensions:	Width: 54 cm Depth: 68,3 cm Height: 54,7 cm
Weight:	36,00 kg

OMNITRONIC Distance Tube Subwoofer/Satellite 100cm

Maximum carrying capacity:	35 kg
Attachment system:	Ø 35mm
Type (general stands):	Distance tube
Material:	Steel
Color:	Black
Dimensions:	Height: 100 cm

	Diameter: Ø 3,5 cm
Weight:	0,78 kg

OMNITRONIC Speaker cable XLR 2x1.5 3m bk

Cable construction:	2 x 2,5 mm² speaker cable
Cable length:	3 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black

OMNITRONIC XLR Cable 3-pin 10m bk

Cable construction:	Audio cable
Cable length:	10 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	0,46 kg