

EUROLITE Set 5x LED SLS-6 TCL Spot + Soft Bag

5x flat spotlight with 6 x 8 W 3in1 LED with RGB color mixing including soft bag

Art. No.: 20000426

GTIN: 4026397302875



Features:

- Slim design for space-saving applications
- DMX and power terminals intelligently designed for easy wiring
- 6 LEDs 8 W high-power 3in1 R/G/B (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 2 integrated show programs
- Direct color selection for 16 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Fixtures available for EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 16°
- With mounting bracket
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand
- <p>EUROLITE SB-18 Soft Bag
- <h2 class="featureSatz">Practical soft bag for 4 PRO Pixel Slim PAR-12/ SLS-400</h2>Made of easy-care nylon
- With Outside pocket
- With dividers

Logistic

EAN / GTIN: 4026397302875

Weight: 7,60 kg

Length: 0.46 m

Width: 0.36 m

Height: 0.27 m

- With 5 device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps

Technical specifications:

Weight: 6.40 kg

EUROLITE LED SLS-6 TCL Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 0.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	6 x 8 W high-power 3in1 R/G/B (homogenous color mix)
Flash rate:	0.5 - 23 Hz
DMX channels:	2; 3; 4; 5; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Fixtures available for:	EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	30°
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Material:	Plastic; ABS Acrylonitrile butadiene styrene
Dimensions:	Width: 22 cm Depth: 11 cm Height: 21 cm
Weight:	1.16 kg

Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm ² H05VV-F
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-18 Soft Bag

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Textile
Color:	Black
Dimensions:	Width: 47 cm Depth: 24 cm Height: 30 cm
Weight:	0.60 kg

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x user manual