

EUROLITE Set 5x LED SLS-7 HCL Spot + Soft Bag

5x LED spotlight with RGBAW+UV color mixing including soft bag

Art. No.: 20000427

GTIN:







List price: 624.75 €

incl. 19% VAT.

Features: Logistic

EUROLITE LED SLS-7 HCL Floor

Flat LED spotlight with RGBWA+UV color mixing, incl. IR remote control

- Slim design for space-saving applications
- Enjoy perfect solid and pastel colors plus ultra violet thanks to 6-color mixing
- DMX and power terminals intelligently designed for easy wiring
- 7 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- 2 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6;
 LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 17°
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- Available in various colors
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x user manual

EUROLITE SB-18 Soft Bag

Practical soft bag for 4 PRO Pixel Slim PAR-12/ SLS-400

- Made of easy-care nylon
- With Outside pocket
- With dividers
- With 5 device compartments
- High-quality workmanship with textile, black
- Interior with foam padding
- 2 carrying straps

Technical specifications:

Weight: 7,50 kg

EUROLITE LED SLS-7 HCL Floor

Power consumption: Polassification: IP20	Power supply:	100-240 V AC, 50/60 Hz
Protection class: Protection class I Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Power output: 1 x IEC connector (F) mounting version Fuse: 5 x 20 mm, T 0,5 A fuse replaceable Lamp type: LED lamp LED type: 7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 2; 3; 4; 6; 10 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/10 peak): 17° Beam angle (1/10 peak): Ultra violet (UV) 400 nm	Power consumption:	20 W
Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Power output: 1 x IEC connector (F) mounting version Fuse: 5 x 20 mm, T 0,5 A fuse replaceable Lamp type: LED lamp LED type: 7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 2; 3; 4; 6; 10 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR Av6; LED EASY OPERATOR Av6; LED EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/12 peak): 17° Beam angle (1/10 peak): Ultra violet (UV) 400 nm	IP classification:	IP20
version power supply cord with safety plug (provided) Power output: 1 x IEC connector (F) mounting version Fuse: 5 x 20 mm, T 0,5 A fuse replaceable Lamp type: LED lamp LED type: 7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 2; 3; 4; 6; 10 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR Ax6; LED EASY OPERATOR Ax6; LED EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/12 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	Protection class:	Protection class I
Fuse: 5 x 20 mm, T 0,5 A fuse replaceable Lamp type: LED lamp LED type: 7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 2; 3; 4; 6; 10 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light 'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	Power connection:	version power supply cord with safety plug
LED lamp LED type: 7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 2; 3; 4; 6; 10 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	Power output:	1 x IEC connector (F) mounting version
LED type: 7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 2; 3; 4; 6; 10 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/12 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	Fuse:	5 x 20 mm, T 0,5 A fuse replaceable
(homogenous color mix) Flash rate: 0 - 20 Hz DMX channels: 2; 3; 4; 6; 10 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	Lamp type:	LED lamp
DMX channels: 2; 3; 4; 6; 10 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	LED type:	5 ,
DMX input: 3-pin XLR (M) mounting version 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	Flash rate:	0 - 20 Hz
DMX output: 3-pin XLR (F) mounting version 1 x cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	DMX channels:	2; 3; 4; 6; 10
Cooling: Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): Ultra violet (UV) 400 nm	DMX input:	3-pin XLR (M) mounting version
Control: Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control Preprogrammed in: Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	DMX output:	3-pin XLR (F) mounting version
master/slave function; IR remote control Preprogrammed in: Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	Cooling:	1 x cooling fan
LED EASY OPERATOR 4xs; LED EASY OPERATOR 4xs; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Projection: Flicker-free Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	Control:	
Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	Preprogrammed in:	LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY
Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	Projection:	Flicker-free
Beam angle (1/10 peak): 39° Wavelength: Ultra violet (UV) 400 nm	Beam angle:	17°
Wavelength: Ultra violet (UV) 400 nm	Beam angle (1/2 peak):	17°
	Beam angle (1/10 peak):	39°
Housing color: Black	Wavelength:	Ultra violet (UV) 400 nm
	Housing color:	Black

Attachment system:	Double bracket
Display type:	Monochrome 4 digit 7-segment LED display
Transport aid:	Rubber feet
Material:	ABS Acrylonitrile butadiene styrene; metal
Dimensions:	Width: 22 cm Depth: 11 cm Height: 21 cm
Weight:	1,38 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	5 x Ø11mm
Material:	Metal, 2 mm
Color:	Black
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

EUROLITE SB-18 Soft Bag

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Textile
Color:	Black
Dimensions:	Width: 47 cm
	Depth: 24 cm
	Height: 30 cm
Weight:	0,60 kg