

## EUROLITE Set 2x LED KLS-180 + 2x LED WF-40 + DMX LED Color Chief Controller

2x Compact Light Set, 2x Projection effect for water reflections including DMX lighting desk

GTIN:



**List price: 1486.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED KLS-180 Compact Light Set

Bar with 4 RGBW spots and 4 white strobe LEDs, with QuickDMX connector (XLR)

- Crossbar with integrated DMX control unit and stand sleeve
- Compact lightweight
- Color blend stepless; color change adjustable; colors preset; Dimmer electronic
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional)
- Preprogrammed in LED PC-Control 512; Light Captain; Light J; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 9°
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: On stand

#### spotlight

- 4 powerful LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)<BR>4 spots controlled separately

#### bar

- 4 powerful LEDs 1 W SMD 8072 cold white (CW)<BR>LEDs controlled separately

#### Package contents

- 1 x spotlight, 1 x bag, 1 x remote control, 1 x battery, 1 x power cord, 1 x user manual

### Logistic

## EUROLITE LED WF-40 Water Effect

Projection effect for water reflections, with RGBW color mixing & DMX

- Static and moving water effects with a 3D look in vibrant colors
- 1 powerful LED 40 W COB (chip-on-board) 4in1 QCL RGBW
- Focus manual
- Dimmer electronic; color blend stepless; Rotation speed stepless; color change adjustable
- Beam effect; strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; stand-alone; master/slave function
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; Colorchief
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Suspended; on stand

### Package contents

- 1 x light effect, 1 x power cord, 1 x user manual

## EUROLITE DMX LED Color Chief Controller

DMX lighting desk with innovative control concept for LED spotlights

- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Can transmit up to 240 DMX channels
- (19") 48.3 cm rack installation 3 U
- Programmable 24 scenes/chases distributed over 1 page/s
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

### Package contents

- 1 x controller, 1 x user manual, 1 x external mains adapter

## Technical specifications:

---

### EUROLITE LED KLS-180 Compact Light Set

|                    |  |
|--------------------|--|
| Power supply:      | 100-240 V AC, 50/60 Hz   |
| Power consumption: | 80 W   |
| IP classification: | IP20   |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output:      | 1 x IEC connector (F) mounting version   |

|                         |   |
|-------------------------|---|
| Fuse:                   | 5 x 20 mm, T 1 A fuse replaceable   |
| Lamp type:              | LED lamp  |
| Flash rate:             | 0,5 - 20 Hz   |
| DMX channels:           | 3; 4; 8; 21   |
| DMX input:              | 3-pin XLR (M) mounting version  |
| DMX output:             | 3-pin XLR (F) mounting version  |
| Cooling:                | Passive convection cooling  |
| Control:                | Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional) |
| Preprogrammed in:       | LED PC-Control 512; Light Captain; Light´J; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief   |
| Projection:             | Flicker-free  |
| PWM frequency:          | 9000 Hz   |
| Beam angle:             | 9°  |
| Beam angle (1/2 peak):  | 9°  |
| Beam angle (1/10 peak): | 18°   |
| Housing color:          | Black   |
| Attachment system:      | Mounting bracket  |
| Display type:           | Monochrome 4 digit 7-segment LED display  |
| Dimensions:             | Width: 60,5 cm<br>Depth: 14 cm<br>Height: 23 cm   |
| Weight:                 | 4,85 kg   |
| Noise classification:   | Class 0 (no noise at all)   |
| Photobiological safety: | Risk Group 0  |
| Spotlight               |   |
| LED type:               | 4 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)   |
| Remote control          |   |
| Battery:                | 1 x button cell 3.0 V CR2025 lithium manganese built-in   |
| Bar                     |   |
| LED type:               | 4 x 1 W SMD 8072 cold white (CW)  |
| Legal specifications    |   |
| Special product:        | Not designed for household room illumination  |
| Intended use:           | Show effect lighting  |

#### **EUROLITE LED WF-40 Water Effect**

|                    |                        |
|--------------------|------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz |
| Power consumption: | 25 W                   |
| IP classification: | IP20                   |
| Protection class:  | Protection class I     |

|                          |  |
|--------------------------|--|
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug included |
| Device fuse:             | 5 x 20 mm, T 1 A fuse replaceable  |
| Lamp type:               | LED lamp   |
| LED type:                | 1 x 40 W COB (chip-on-board) 4in1 QCL RGBW   |
| Flash rate:              | 2,5 - 19 Hz  |
| Equipment:               | Focus manual   |
| DMX channels:            | 9  |
| DMX input:               | 1 x 3-pin XLR (M) mounting version   |
| DMX output:              | 1 x 3-pin XLR (F) mounting version   |
| Cooling:                 | Passive convection cooling   |
| Control:                 | DMX; sound to light via microphone; stand-alone; master/slave function                         |
| Preprogrammed in:        | Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; Colorchief               |
| Beam angle (1/2 peak):   | 30°  |
| Housing color:           | Black matte  |
| Attachment system:       | Mounting bracket   |
| Display type:            | Monochrome 4 digit 7-segment LED display   |
| Material:                | Metal  |
| Dimensions:              | Width: 27,7 cm<br>Depth: 25,2 cm<br>Height: 18,7 cm  |
| Weight:                  | 3,32 kg  |
| Noise classification:    | Class 2 (slight noise)   |
| Power cord               |  |
| Cable construction:      | 3 x 0,75 mm² H05VV-F   |
| Cable length:            | Approx. 1,4 m  |
| Mounting bracket         |  |
| Diameter mounting holes: | 3 x Ø10mm  |
| Material:                | Metal, 2 mm  |
| Legal specifications     |  |
| Special product:         | Not designed for household room illumination   |
| Intended use:            | Show effect lighting   |

#### **EUROLITE DMX LED Color Chief Controller**

|                    |   |
|--------------------|---|
| Power supply:      | 100-240 V AC, 50/60 Hz<br>9V DC 800 mA  |
| Power consumption: | 7,2 W   |
| IP classification: | IP20  |
| Protection class:  | Protection class III  |
| Power connection:  | Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |

|                          |   |
|--------------------------|---|
| Programs:                | Programmable 24 scenes/chases distributed over 1 page/s                         |
| DMX channels:            | Output 240  |
| DMX output:              | 1 x 3-pin XLR (F) mounting version  |
| Control:                 | DMX; sound to light via RCA (F) mounting version; sound to light via microphone |
| Housing color:           | Black   |
| Available storage media: | USB devices (FAT 32)  |
| USB port:                | Type A  |
| Color:                   | Black   |
| PC connect:              | , firmware can be updated   |
| Housing design:          | (19") 48.3 cm rack installation 3 U<br>Desktop console housing                  |
| Dimensions:              | Width: 48,3 cm<br>Depth: 13,35 cm<br>Height: 8,5 cm                             |
| Weight:                  | 2,25 kg   |
| Noise classification:    | Class 0 (no noise at all)   |